

(November 1983)
(Formerly 9-331)

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT COMMISSION

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. LC-071066
2. NAME OF OPERATOR The Petroleum Corporation of Delaware ✓	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 3811 Turtle Creek Blvd., Suite 350, Dallas, Texas 75219-4419	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2310' FSL & 1892' FWL of Sec. 12, T-26-S, R-29-E Unit Letter K NE/4, SW/4	8. FARM OR LEASE NAME Brushy 12 Federal
14. PERMIT NO. API No. 30-01525519	9. WELL NO. #2
15. ELEVATIONS (Show whether OF, RI, GR, etc.) 2969.1 2972.5' GR 2983.5' KB	10. FIELD AND POOL, OR WILDCAT 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Brushy Draw Delaware Sec. 12, T-26-S, R-29-E
	12. COUNTY OR PARISH Eddy Co.
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐	PUMP OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Drilling and setting casing ☒	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

16. PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well @ 12:15 p.m. CDT 12/18/85.

Drilled 11" hole to 720' KB. Set 8-5/8" 24# J-55 csg @ 704' KB.
Cemented w/ 425 sx class C w/ 2% CaCl. Circulated 10 sx to surface.

Drilled 7-7/8" hole to 5500' KB 12/31/85. Ran Schlumberger Wireline logs.
Set 135 jts 5-1/2" 15.5# K-55 csg with 18 centralizers and 2 cement baskets @ 5491' KB. Cemented w/ 225 sx class C w/ 6# salt & 1/4# Flocele.
Cemented thru bottom DV tool @ 4674' KB w/ 275 sx Trinity Lite Water w/ 1/2# Flocele. Cemented thru top DV tool @ 3763' KB w/ 275 sx class C w/ 6# salt & 1/4# Flocele. Released Rig at 12:30 a.m. CDT 1/5/86.

ACCEPTED FOR RECORD

JAN 15 1986

CAPISRAD, NEW MEXICO

17. I hereby certify that the foregoing is true and correct

SIGNED

TITLE VP - Drilling and Production DATE 1/9/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED BY

JAN 17 1986

O. C. D.

ARTESIA, OFFICE