

SUPPLEMENTAL DRILLING DATA

United Petroleum Corporation
Phillips Federal No. 1
330' FSL & 2063' FEL
Sec. 1, T26S, R29E
Eddy County, N.M.
NM-23765

The following information is in accordance with 'Onshore Oil & Gas Order' No. 1:

1. Surface Formation: Recent

2. Estimated Geological Marker Tops:

Rustler	660'	Lamar 'LS'	3062'	Bell Canyon	3207'
Salt	750'	Delaware 'SS'	3087'	Cherry Canyon	4127'
Base Salt	3150'	Ramsey 'SS'	3122	Brushy Canyon	5527'

3. Mineral Bearing Formation: Delaware - oil

4. Proposed Casing and Cement Program:

13 3/8" Casing - Set approximately 400', 54.5#, J-55, ST&C casing.
Cement to surface with 350 sx cement.

8 5/8" Casing - Set approximately 3200', 24 and 32#, K-55, ST&C casing. Cement sufficient to circulate to surface.

5 1/2" Casing - Set to total depth, 17.0#, K-55, ST&C casing.
Cement sufficient to base of 8 5/8" casing.

5. Pressure Control Equipment: A 3000 psi working pressure double-ram type B.O.P. will be installed on the 8 5/8" casing.

6. Proposed Mud Program:

0 - 400' Fresh water mud. Mud weight 8.5-9.0#. Viscosity 32-34.

400 - 3200' Brine water. Mud weight 10.0#. Viscosity 28-30.

3200 - T.D. Brine water adding starch and drispac for water loss control.

7. Auxiliary Equipment: A kelly cock will be installed on the rig floor while drilling operations are in progress.