

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Artesia, NM 88210

SUBMIT IN TRI  
DATE\*  
on re-

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

4/5F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-23765

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Phillips Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Brushy Draw-Delaware

11. SEC., T., S., M., OR BLK. AND  
SURVEY OR AREA

Sec. 1, T26S, R29E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

RECEIVED BY

JAN 24 1986

O. C. D.  
ARTESIA, OFFICE

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling Well

2. NAME OF OPERATOR

United Petroleum Corporation

3. ADDRESS OF OPERATOR

P.O. Box 2951, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

330' FSL & 2063' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3011' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) 8 5/8" Casing and Cement

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

1/13/86 Total Depth 3155'.

Ran 3155' 8 5/8", 24 and 32#, K-55, ST&C casing and set at 3155'.

Cemented with 800 sx Hal-lite, 10# salt/sk followed by 200 sx Class 'C'  
2% CaCl. Circulated 30 sx to surface. P.O.B. at 6:00 P.M. W.O.C. 18  
hours. Pressure tested B.O.P. and 8 5/8" casing to 800 psi for 30 minutes.

ACCEPTED FOR RECORD

*ACQ*  
JAN 21 1986

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Larry W. Franklin*

TITLE

Agent

DATE 1/20/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side