

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NM OIL, GAS, AND GEOTHERMAL DIVISION
SUBMIT IN TRIP CATH
Drawings (Other instructions on reverse side)
Artesia, NM 88210

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

c15f

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	5. LEASE DESIGNATION AND SERIAL NO. NM-16814
2. NAME OF OPERATOR Challenger Energy, Inc. LaRue and Muncey	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 1262, Artesia, NM 88210	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location on the right in accordance with BLM Survey. See also State 17 below.) At surface 330" FNL & 330' FNL of Section 18	8. FARM OR LEASE NAME Bedena Federal
	9. WELL NO. #2
	10. FIELD AND POOL, OR WILDCAT Brushy Draw Und. Del.
	11. SEC. T., R., M., OR BLM. AND SURVEY OR AREA Sec. 18, T-26S, R-30E
	12. COUNTY OR PARISH Eddy
	13. STATE NM
3035.5 GL	

RECEIVED BY
APR 1 1986
O. C. D.
ARTESIA, OFFICE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF ABANDONMENT		SUBSEQUENT REPORT OF:	
☐ ABANDONMENT	☐ ABANDONMENT	☐ WATER SHUT-OFF	☐ REPAIRING WELL
☐ ABANDONMENT	☐ ABANDONMENT	☐ FRACTURE TREATMENT	☐ ALTERING CASING
☐ ABANDONMENT	☐ ABANDONMENT	☐ SHOOTING OR ACIDIZING	☐ ABANDONMENT*
☐ ABANDONMENT	☐ ABANDONMENT	☐ OTHER casing & cement	☒ X

Notes: Report results of multiple completion on Well Completion or Completion Report and Log form.
*If well is being plugged, give subsurface well log and measured interval depths for all markers and zones pertinent to this work.

Well was spudded on 2/28/86 at 5:00 pm

- 3/1/86 Surface T.D. at 3:15 am
Ran 674' of 13 3/8", 54# casing set at 558'
Cemented with 685 sks Class "C", 2% CaCl, 1/4# flocele, Plug down at 4:45 pm 3/1/86
Circulated 250 sks to pit, Pressure tested 800# for 30 min., Held. WOC 18 hours
- 3/9/86 Intermediate T.D. at 3:45 pm
Ran 3189' of 9 5/8", 36# K-55 casing set at 3175'
Cemented with 300 sks Class "C", with 2% CaCl, 1/4# flocele, Plug down at 4:00 am 3/10/86, Did not circulate, Pressure tested 1000# for 30 min., Held, WOC 18 hours
- 3/19/86 Well was drilled to a total depth of 6500' at 5:30 pm
Ran 6516' of 5 1/2", 17# K-55 set at 6500'
- 3/21/86 Cemented first stage with 200 sks Halliburton Lite, 1/4# flocele, 5# salt, and 415 sks of Class "H", 2# salt, 1/4# flocele, 4/10% Halade-4, 3/10% CFR-3, Plug down 7:45 am
Cemented second stage with 420 sks Class "H" with 3# salt, 1/4# flocele, 4/10% Halade-4, 3/10% CFR-3, Plug down 12:30 pm
Pressure tested 1000# for 30 min., Held

ACCEPTED FOR RECORD

Gurl
MAR 31 1986

I, the undersigned, certify that the foregoing is true and correct.

SIGNED <i>Dickie Gurl</i>	TITLE <i>Production Clerk</i>	DATE <i>3/26/86</i>
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE
CONCLUSIONS OF APPROVAL, IF ANY:		

*See Instructions on Reverse Side