

UNITED STATES OF AMERICA
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
BASS ENTERPRISES PRODUCTION CO.
3. ADDRESS OF OPERATOR
P.O. BOX 2760, Midland, Texas 79702-2760
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 760' FNL & 2080' FEL unit Letter B.
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same As Above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) DST #1 & 5-1/2" casing.

SUBSEQUENT REPORT OF:

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-30-87 DST #1 4398'- 4327' (71') RAMSEY

IF 3 min with a weak to fair blow in 2 min, max pressure 10 oz ISI 30 min, no GTS
FF 240 min, opened with weak blow, increased to fair blow in 1 hour and 45 minutes,
continued to increase. Maximum 4.25 psi in four hours. FSI 30 min, no GTS

Recovered: 3470' gas in DP
710' HG&SOCD mud

Sample Chamber: 100 psi 0.716 cu.ft.

600 cc drilling mud and formation water

340 cc free oil API 42° @ 60° F

PRESSURES

IHP 2321 psi FF 144-226 psi
IF 144-123 psi BHT = 90° F
ISI 535 psi FSI 720 psi

OVER

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. L. Hutchens

TITLE Sr. Prod. Clerk

DATE

October 5, 1987

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE ACCEPTED FOR RECORD

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

SPC : 13861 C - 347-166

Ran 113 joints of 5- $\frac{1}{2}$ " 14#/ft K-55 ST&C with differential fill guide shoe, Differential fill float collar, 5 centralizers.

Cemented with 175 sx Class "C" Neat 1.32 ft³/sk, 14.8 ppg. Plug down @3:15 AM CST 10-2-87.
Bumped plug to 500 psi over displacement pressure. Floats held. Full returns throughout job.

Released rig 7:00 AM CST 10-2-87

Waiting on Completion.