

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved by
Budget Bureau No. 1004-101
Expires August 31, 1985

45P

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Texaco Producing Inc.

3. ADDRESS OF OPERATOR
PO Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

Unit Letter G, 1745' FNL & 2121' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
2970' GR

NOV 18 '87
O. C. D.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.
NM-17225-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Salt Mountain 25 Fed.

9. WELL NO.
3Y

10. FIELD AND POOL OR WILDCAT
Brushy Draw Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
S25, T26S, R29E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
|-------------------------|--------------------------|---|-------------------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | WATER SHUT-OFF | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | FRACTURE TREATMENT | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | SHOOTING OR ACIDIZING | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | (Other) Drilling | <input checked="" type="checkbox"/> |
| (Other) | <input type="checkbox"/> | (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud 14 3/4" hole at 8:00 PM, 10/15/87
Ran 12 jts. 11 3/4", 42#, H-40, 8RS casing, set at 500'.
Ran 71 jts. (2989') 8 5/8", 32#, J-55, LT & C casing, set at 3000'.

- 1) Ran 132 jts. (5389') 5 1/2", 15.5#, J-55, ST & C casing, set at 5400'. DV at 3625'.
- 2) Cement 1st stage with 450 sxs. LW with 1/4# Floc. followed by 250 sxs. Class "H" with 1/4# Floc. Circulated 36 sxs. cement.
- 3) Cement 2nd stage with 500 sxs. LW with 1/4# Floc. followed by 300 sxs. Class "H" with 1/4# Floc. Circulate 135 sxs. Pressured up with 61 bbls. Disp. gone leaving cement at 2785' in casing.
- 4) Released rig at 8:00 PM, 10/27/87.

ACCEPTED FOR RECORD

NOV 17 1987

SJS
CARISBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

397-3571

SIGNED

TITLE Hobbs Area Superintendent DATE 10/30/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side