

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

RECEIVED
OTHER INFORMATION
REVERSE SIDE

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☒ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other ☐

2. NAME OF OPERATOR
BETTIS, BOYLE & STOVALL

3. ADDRESS OF OPERATOR
P. O. BOX 1240, GRAHAM, TEXAS 76046

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface 660' FNL & 860' FEL of Section 8, T25S, R29E
At top prod. interval reported below
At total depth

14. PERMIT NO. DATE ISSUED

15. DATE SPUDDED 3-30-88 16. DATE T.D. REACHED 6-7-88 17. DATE COMPL. (Ready to prod.) 11-11-90 workover 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 2934.4 19. ELEV. CASINGHEAD 2937

20. TOTAL DEPTH, MD & TVD 13,879 21. PLUG, BACK T.D., MD & TVD 13,650 22. IF MULTIPLE COMPL., HOW MANY* -2- 23. INTERVALS DRILLED BY 0-13,777 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 12,394 - 12,404, Atoka; 13,604 - 13,614, Morrow; 13,158 - 13,163, Morrow

25. WAS DIRECTIONAL SURVEY MADE NO
26. TYPE ELECTRIC AND OTHER LOGS RUN None ran after dual completion
27. WAS WELL CORED NO

CASING RECORD (Report all strings set in well)					
CASINO SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
20"	94# & 133#	637'	26"	1800 sx - circulated	0
13 3/8"	68#	2875'	17 1/2"	2700 sx - circulated	0
9 5/8"	43.5, 47 & 53	5# 10,100'	12 1/4"	900 sx	0

LINER RECORD					TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
7 5/8"	9785	13,777	900 sx		2 7/8"	12,372	12,340

31. PERFORATION RECORD (Interval, size and number)		32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
12,394 - 12,404, 41 holes;		DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
13,604 - 13,614, 34 holes;		13,604-13,614	acidized w/3000 gallons
13,158 - 13,163, 21 holes;			7 1/2%, 120 balls

33.* PRODUCTION							
DATE FIRST PRODUCTION 11/11/90		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing				WELL STATUS (Producing or shut-in) PRODUCING	
DATE OF TEST 12/1/90	HOURS TESTED 24	CHOKE SIZE 14/64	PROD'N. FOR TEST PERIOD	OIL—BBL. 0	GAS—MCF. 157	WATER—BBL. 0	GAS-OIL RATIO
FLOW. TUBING PRESS. 640	CASING PRESSURE 0	CALCULATED 24-HOUR RATE	OIL—BBL. 0	GAS—MCF. 157	WATER—BBL. 0	OIL GRAVITY-API (CORR.)	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) sold
35. LIST OF ATTACHMENTS NONE
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Jim Pizon TITLE Production Analyst DATE 12/4/90

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored in, and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38.

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Lamar LM.	2860'	2906'	Limestone	Lamar LM.	2860'	
Canyon	2906'	3756'	Sandstone w/Shale & Limestreaks	Bell Canyon	2906'	
Cherry Canyon	3756'	5390'	Sandstone w/Lime Streaks	Cherry Canyon	3756'	
Brushy Canyon	5390'	6656'	Sandstone w/Lime & Shale Streaks	Brushy Canyon	5390'	
Bone Springs	6656'	7566'	Lime, Shale & Sand	Bone Springs	6656'	
1st Bone SpringsSD	7566'	8384'	Sand w/Shale & Lime Streaks	1st Bone Springs	7566'	
2ns Bone SpringsSD	8384'	9452'	Sand w/Lime Streak	2ns Bone Springs	8384'	
3rd Bone SpringsSD	9452'	9852'	Sand & Shale	3rd Bone Springs	9452'	
of camp	9852'	12164'	Limestone w/Shale Streaks	Wolcamp	9852'	
Strawn	12164'	12381'	Sand & Lime	Strawn	12164'	
Upper Atoka	12381'	12491'	Sand w/Shale & Lime Streaks	Upper Atoka	12381'	
Atoka Bank	12491'	12518'	Limestone	Atoka Bank	12491'	
Middle Atoka	12518'	12552'	Shale Sand & Limestone	Middle Atoka	12518'	
Lower Atoka	12552'	12986'	Shale w/Sand & Lime Streak	Lower Atoka	12552'	
Upper Morrow	12986'	13366'	Shale & Sand	Upper Morrow	12986'	
Middle Morrow	13366'	13644'	Shale & Sand	Middle Morrow	13366'	
Lower Morrow	13644'	13650' T.D.	Sand, Shale, Chert & Lime	Lower Morrow	13644'	
				T.D.	13650'	