

45F

Form 3160-5
(November 1983)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
SUBMITTING OFFICE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

Nov 15 11 17 AM '88

RECEIVED

DEC 12 '88

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Bettis, Boyle & Stovall ✓

3. ADDRESS OF OPERATOR
P.O. Box 1240, Graham, TX 76046

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1980' FSL & 1980' FEL, NW/4Se/4, Unit Letter J

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)
3457.3' GR

5. LEASE DESIGNATION AND SERIAL NO.
NM-29234

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Lotos Federal

9. WELL NO.
-1-

10. FIELD AND POOL, OR WILDCAT
Und. S. Sand Dunes Lower

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 9, T24S, R31E

12. COUNTY OR PARISH
Eddy

13. STATE
N.M.

ARTESIA, OFFICE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- (Other)

- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- ABANDON*
- CHANGE PLANS

- WATER SHUT-OFF
- FRACTURE TREATMENT
- SHOOTING OR ACIDIZING
- (Other)

- REPAIRING WELL
- ALTERING CASING
- ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/10 - 10/11/88 Ran 274 jts. 9 5/8", 53.5 + 47#, P-110 to 11,674'. Cement with 750 sx. Poz mix. Set in 12 1/4" hole.

11/8/88 Ran 95 jts., 5 1/2", 23#, P-110 shoe at 15,276, top of liner at 11,480', cemented with 400 sx. Class H, set in 8 1/2" hole.

11/9/88 Squeeze top of liner with 150 sx. Class H, RTTS set 15 10,863

11/10/88 Tested top of cement to 3300 psi, held for 2 hrs..

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Production Assistant

DATE

Nov. 11, 1988

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 6 1988

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO