Submit 3 Copies State of New Mexico to Appropriate Energy, Minerals and Natural Resources Department District Office District Office	Form C-103
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION, DLYISION P.O. Box 2088 WELL API NO. 30-015-261	105
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease	
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease N	
0. C. C. C. V-1085	
SUNDRY NOTICES AND REPORTS ON WESSAS OFFICE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	reement Name
1. Type of Well: Change well East Apple Stat OIL WELL OTHER status to oil.	te Unit
2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION 1	
3. Address of Operator9. Pool name or Wildcat105 South 4th St., Artesia, NM 88210Wildcat	
4. Well Location Unit LetterG :1980 Feet From The North Line and1980 Feet From The	East Line
Section 5 Township 26S Range 28E NMPM Edd	dy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3026' GR	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG	
PULL OR ALTER CASING	—
OTHER: OTHER: Perforate, Treat	X
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting work) SEE RULE 1103.	
 7-18-89. Acidized perfs 6812-26' w/2000 gals 15% NEFE acid and 10 ball sealers 7-21-89. Acidized perfs 6209-18' w/1500 gals 7½% Spearhead acid. (Amended treat 7-28-89. Frac'd perfs w/20000 gals 40# Mini-Max III and 40000# 20/40 sand + 5 Recovered load and tested well. 8-8-89. Set cement retainer at 7138'. Cemented w/75 sx Class C. Squeezed to 8-10-89. Drilled retainer and 15' cement. Circulated. Drilled thru perfs 62 out to RBP at 6270'. Circulated sand off top of plug. Pulled RBP from 6270'. perforated 7621-39' w/12 .42" holes as follows: 7621, 22, 23, 24, 25, 30, 31, and 7639'. Dropped bar. No show at surface. Acidized perfs 7621-7639' (12 H gals 7½% Spearhead acid. 	atment report.) 50 tons CO2. o 2500 psi. 209-18'. Cleaned . WIH and , 32, 33, 35, 36,
8-23-89. WIH and perforated 7911-7955' w/17 .42' holes as follows: 7911, 12, 18, 19, 45, 46, 47, 48, 49, 50, 53, 54 and 7955'. Acidized perfs 7911-7955' w/ Spearhead acid.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SKONATURE HURANDE DAVIDAT THE Production Supervisor DAT	пе8-25-89
TYPE OR PRINT NAME Juanita Goodlett TEL	EPHONE NO. 505/748-1471
(This space for State Use) ORIGINAL SIGNED BY	

•

CONDITIONS OF APPROVAL, IF ANY:

_