

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLY
(Other instructions
verse side)

TE
re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 30886-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yeso Hills Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat BS

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 18, T-26-S, R-25-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Strata Production Company

AUG -9 '90

3. ADDRESS OF OPERATOR

648 Petroleum Building Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations.
See also space 17 below.)
At surface

460' FSL and 1780' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OK, etc.)

3839' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing design w/ cement volume X

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- 1) Set 9 5/8", 36# K55 csg to 1263'. Cemented w/ 730 sx "Premium Plus" w/ 1250# Thixset A. Circulated cement to sfc.
- 2) TD hole @ 6199'. BHL @ 6097' MD was 84.5 deg, 4757.8' TVD, 1702' VS N 6.2 W.
- 3) Set 150 jts 5 1/2", csg w/ Lynes inflatable pkr @ 4625'. Cmt thru DV tool w/ 500 sx "premium" & 500 sx 85/15 "premium pozmix". Circulate 20 sx to pit. PD @ 12:15 pm, 4-25-90.

Aug 3 10 27 AM '90

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

James E. Mc Clelland

TITLE

Vice President

DATE

8-2-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side