

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDAY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM 54291

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gehrig Federal #2

9. API Well No.

30-015-26995

10. Field and Pool, or Exploratory Area

Brushy Draw Delaware

11. County or Parish, State

Eddy Co., NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hanagan Petroleum Corporation

3. Address and Telephone No.

P.O. Box 1737 - Roswell, NM 88202-1737 505-623-5053

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 330' FEL Sec. 9, T26S, R29E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Surface casing/BOP
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spud well w/United Drilling Co. Rig #3 @ 12:30 PM 12/29/92 - Notified BLM-Carlsbad.
2. Drilled 12 1/4" hole to 440'.
3. Ran 10 jts. of new 8 5/8" J-55 24#/ft. casing to TD.
4. Cemented 8 5/8" casing w/290 sx. Howco Prem. Plus cement + 2% CaCl, plug down @ 4:30 AM 12/30/92, pressure up to 800# plug held ok, circulate 60 sx. cement to pit. Witnessed by Don Early BLM - Carlsbad.
5. Wait on cement 18 hours.
6. Nipple up BOP and pressure test to 1000# for 30" using rig pumps, held good.
7. Drilled out shoe @ 10:30 PM 12/30/92. Pressure up to 500#/15", held ok.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Vice Pres.

Date 12/31/92

(This space for Federal or State office use)

Approved by [Signature]

Title _____

Date _____

Conditions of approval, if any:

Title 18 U.S.C. Section 1001. Any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations in any matter within its jurisdiction.

*See instruction on Reverse Side