

45F
Dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 3001527008
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2372 & V-2507

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Cactus 16 State
2. Name of Operator Bettis, Boyle & Stovall	8. Well No. -1-
3. Address of Operator P. O. Box 1240, Graham, TX 76450	9. Pool name or Wildcat Wildcat Brushy Canyon

AUG 20 1992
O.C.D.
MIRU Norton

4. Well Location
Unit Letter C : 2310 Feet From The West Line and 330 Feet From The North Line
Section 16 Township 24S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3492 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: _____ <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: _____ <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/17/92 MIRU Norton Drilling Rig #12, spudded well.
 6/21/92 Ran 18 jts. of 13-3/8", 54# csg. in a 17-1/2" hole to 626', cemented with 470 sx Howco Lite +2% CC+ 200 sx Class C + 2% CC. Circ. cement to pit. WOC 10 hrs.
 6/29/92 Ran 108 jts. 8-5/8", 24# & 32# csg. in a 12-1/4" hole to 4250', cemented with 1450 sx Howco prem. Lite + 2 sx Prem + cement, circ cement to sur., WOC 12 hrs.
 7/08/92 Run Dual Induction, Density Neutron logs to TD 8450'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kim Ligon TITLE Production Analyst DATE 8/17/92
 TYPE OR PRINT NAME Kim Ligon TELEPHONE NO. 817-549-0780

(This space for State Use)

APPROVED BY MIKE WILLIAMS TITLE SUPERVISOR, DISTRICT II DATE SEP 16 1992
 CONDITIONS OF APPROVAL, IF ANY: