Form: 3160-5 (June 1990)

Subsequent Report

## UNITED STATES DEPARTMENT OF THE INTERIOR

NM OIL CONS COMMISSION 

FORM APPROVED

Non-Routine Fracturing

Conversion to Injection

(Note: Report results of multiple completion on Well

Water Shut-Off

Dispose Water

Budget Bureau No. 1004-0135

SUNDRY NOTICES  Do not use this form for proposals to d	LAND MANAGEMENT AND REPORTS ON W rill or to deepen or reentr OR PERMIT—" for such pr	v to a different restervoir	5. Lease Designation and Serial No. NM-29234 6. If Indian, Allottee or Tribe Name
SUBMIT	T IN TRIPLICATE	Shad, New	7. If Unit or CA, Agreement Designation
1. Type of Well    XX Oil	1 8, T24S, R31E	OCT 11.'94  B2-6822 C. D.  ARTESIA, OPPICE	8. Weil Name and No.  Sundance 8 Federal No.  9. API Weil No.  30-015-27229  10. Field and Pool, or Exploratory Area  Undes Delaware  11. County or Parish, State  Eddy County, NM
CHECK APPROPRIATE BOX(	s) TO INDICATE NATU	RE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
Notice of Intent	Abandonmer Recompletio		Change of Plans

Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugging Back

Casing Repair

Altering Casing

🕅 <sub>Other</sub>TD & Production Csa

Drilled 7-7/8" hole to 8220'. TD reached @ 1645 hrs CDT 8/7/94. Logged well w/ Western Atlas. Ran 184 jts 5-1/2", 15.5# & 17#, J-55 LT&C casing. Float shoe @ 8220'. Float collar @ 8173'. Stage tools @ 3876' & 6009'. BJ cemented 1st stage w/ 575 sx Class "H" + 5 pps ECl + 2.5% KCl + .6% FL62 + .2% CD32 + .2% R3 @ 15.6 ppg. Drop plug & displace cement. Drop bomb and open DV tool @ 6009'. Circulate 5 hrs between stages. Recovered 155 sx excess cement. Cement 2nd stage w/ 740 sx Cl "H" + 5 pps ECl + 2.5% KCl + .6% FL62 + .2% CD32 + .2% R3. Drop plug & displace cement. Drop bomb & open DV tool @ 3876'. Circulate 5 hrs between stages. Recovered 135 sx excess cement. Cement 3rd stage w/ 400 sx BJ Lite @ 12.7 ppg. Followed by 100 sx Class "C" @ 14.8 ppg. Plug down @ 0730 hrs CDT 7/9/94. Recovered 15 sx excess cement. ND BOP's and make cut-off. Weld on wellhead and test to 2500 psi.

14. I hereby certify the the foregoing is type and correct  Signed Manhard May	Title Division Operations Manager	9/8/94
(This space for Federal or State office use)		
Approved by	Title	Date
		<i>5</i> 1/

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.