Form 3160-5 (June 1990)

N.M. Oil Cons. vision 811 S. 1st Street

FORM APPROVED
Budget Bureau No. 1004-0135

UNITED STATES 811 5. 181 Street DEPARTMENT OF THE INTERIOArtesia, NM 88210-2834 BUREAU OF LAND MANAGEMENT

Expires: March 31, 1993

5. Lease Designation and Serial No.

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS

NM-29234
6. If Indian. Allouse or Tribe Name

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such pr	Opesais
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designal
I. Type of Weil	
X Oil Gas Weil Other	8. Weil Name and No.
2. Name of Operator	Sundance 8 Federal
Pogo Producing Company	9. API Well No. 30–015–27229
Address and Telephone No. P. O. Box 10340, Midland, TX 79702-7340	AUG 0 5 1990 30-015-27229 10. Field and Pool, or Exploratory Are
Location of Well (Footage, Sec., T., R., M., or Survey Description)	Sand Dunes Del. S.
	11. County or Parish, State
1650' FNL & 330' FWL, Section 8, T24S, R31E	Eddy County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATUL	
TYPE OF SUBMISSION	TYPE OF ACTION
Notice of Intent	
Recompletio	
X Subsequent Report Plugging Bac Casing Repa	
Final Abandonment Notice	
X Other Ad	d Perfs Dispose Water
	(Note: Report results of multiple completion or Completion or Recompletion Report and Logic
give subsurface locations and measured and true vertical depths for all markers and zones pe	rtinent to this work.)*
t RBP @ 6700'. Load & test ok. Perf'd 5 f 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa:	5-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP
t RBP @ 6700'. Load & test ok. Perf'd 5 f 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa:	5-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP
t RBP @ 6700'. Load & test ok. Perf'd 5 f 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa:	5-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP
t RBP @ 6700'. Load & test ok. Perf'd 5 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa:	G-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
t RBP @ 6700'. Load & test ok. Perf'd 5 f 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa:	FIED FOR SECOND (Compared to this work.) 6-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
t RBP @ 6700'. Load & test ok. Perf'd 5 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 5700'. On production w/ combined Delawa:	G-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
give subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface location with the subsurface locations and subsurface locations and subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and measured and true vertical depths for all markers and zones per consistency of the subsurface locations and true vertical depths for all markers and zones per consistency of the subsurface locations and true vertical depths for all markers and zones per consistency of the subsurface locations and true vertical depths for all markers and zones per consistency of the subsurface locations and true vertical depths for all markers and zones per consistency of the subsurface locations and true vertical depths for all markers and zones per consistency of the subsurface locations and true vertical depths for all markers and zones per consistency of the subsurface locations and zones per consistency of the subsurface locations are consistency of the subsurface locations and zones per consistency of the subsurface locations are consistency of the subsurface locations and zones per consistency of the subsurface locations are consistency of the subsurface locatio	FIED FOR SECOND (Compared to this work.) 6-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
TRBP @ 6700'. Load & test ok. Perf'd 5 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 5700'. On production w/ combined Delawa:	G-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
TRBP @ 6700'. Load & test ok. Perf'd 5 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 5700'. On production w/ combined Delawa:	FIED FOR SECONDARY BLM 6-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
t RBP @ 6700'. Load & test ok. Perf'd 5 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawar 6480'-6504' 4/22/95.	G-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
t RBP @ 6700'. Load & test ok. Perf'd 5 f 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa. 6480'-6504' 4/22/95.	FIED FOR SECONDARY BLM 6-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
t RBP @ 6700'. Load & test ok. Perf'd 5 f 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa 6480'-6504' 4/22/95.	S-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'
t RBP @ 6700'. Load & test ok. Perf'd 5 f 120° spiral phase on 2/7/95. Acidize ac'd w/ 27,860# 16/30 sand. Pump to tes 6700'. On production w/ combined Delawa: 6480'-6504' 4/22/95.	S-1/2" csg 6480'-6504' w/ 4" csg 2 ed w/ 1000 gals 7-1/2% HCl NeFe. t 2/15/95. 4/18/95 retrieved RBP re perfs 8016'-8081', 7856'-7943'