DEPARTMENT OF THE INTERIOR BUREAU (AND MANAGEMENT

N.M. DI')ist. 2

FORM APPROVED OMB No. 1004-0135

SUBMI	AM-82904 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.			
Type of Well	T IN TRIPLICATE -		on reverse side	
X Oil Well	Gas Well	Other		8. Well Name and No.
Name of Operator			- 10 h	ADELINE ALN FEDERAL #3
Yates Petroleum Co	rporation			9. API Well No.
3a Address		at at		30-015-27244
105 S. 4th Street - A	rtesia, NM 88210	3b. Phone No. (inclu 505-748-1471	ude area code)	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Set Ut. B 660' FNL & 1980' FEL	ec., T.,R., M., or Survey Desc	ription)	OCD AR	WILDCAT DELAWARE 11. County or Parish, State
				}
TYPE OF CHECK A	PPROPRIATE BOX(E	S) TO INDICATE NAT	URE OF NOTICE, REPOR	EDDY
TYPE OF SUMISSION			TYPE OF ACTION	T, OR OTHER DATA
Notice of Intent	Acidize			
		Deepen	Production (Start/Resume)	Water Shut-Off
Subsequent Report	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Final Abandonment Notice	Casing Repair	New Construction	Recomplete	⊠Other Drill
	Change Plans	Plug and Abandon	Temporarily Abandon	perf acidize and frac
3 Describe Proposed at C	Convert to Injection	Plug Back	Mater Disease	
completion or recompletion in a new reclamation, have been completed, SPUD 26 CONDUCTOR HOLE @ SHOE SET AT 556' INSERT FLOA' PREMIUM PLUST + 2% cAc12 (YLI TO 11" AND RESUMED DRILLING, TAILED IN WITH 250 SKS PREMIUM TGGED CEMENT AT 4040'. DRILL DRILL TO 8170'.CIRCULATE - WAI 05/19/01. RAN 194 JTS. (8173.22') VARNISH (83.62') CENTR 400 SX SUPER H .5% HALB (YLD 1.51, WT 14.4). PL 0 SACKS. FLOAT & CSG	vinterval, a Form 3160-4 shall be and the operator has determined 11:30 AM 4/27/01. DRILLING 525 F SET AT 511.35". CEMENTED W D 1.34, WT 14.8). CIRCULATED TOH AND PICKED UP BHA REJUM PLES WITH 2% CaC12 (YLD ED TO 4934". DRILLING 6380" S T ON LOGGERS. CIRCULATR T SET AT 8170". RAN 30 JTS 5-1/2 ALIZED ON JTS. 1ST JC LAD - 344, .4% CFR-3, 5: UG DOWN 7:30 PM. CE HELD OK. CEMENT CIII	reports shall be filed within 30 did filed once testing has been conthat the site is ready for final instance in the site in the s	ays following completion of the involved of impleted. Final Abandonment Notices shat pecition.) 4 HRS. RAN 13 JTS. 13-3/8" H-40 48# (Fig. 12 Miller of the involved of the in	proximate duration thereof. If the proposal is to deepen Attach the Bond under which the work will be performed operations. If the operations results in a multiple all be filed only after all requirements, including 557')CSG., SET AT 570'. TEXAS PATTERN GUIDE E-FLAK (YLD 1.89, WT 12.6). TAILED IN WITH 200 SACKS MADE 400' IN 10-1/2 HRS.38.10'/HR REDUCED HOLE ITE AND SALT. LAID DOWN BHA. RIGGED UP. RS 1ST JOINT ABOVE SHOE THEN EVERY 3RD JOINT. 575' IN 23-1/2 HRS. SURVEY 8025' 1-1/4 CEMENT 2ND STAGE. RELEASED RIG AT 6:00 AM VARNISH (6785.66) RAN 2 JTS 5-1/2" J-55 17# D, & 37TH. JOINT. STATE. CEMENTED N WITH 50 SX PREMIUM 1% COMPONENT TO 1980 PSI FOR 2 MINUTES. CEMENT CIRC. WAITING ON COMPLETION UT.

I hereby certify that the foregoing is true and correct						
Name (Printed/Typed)						
Donna Clack	Operations Technician					
Signature						
- while (last by (y)	Date					
ACCEPTED FOR RELIGIOUS FEDERAL OR STATE OFFICE USE						
Approved by						
ORIG. SGD.) DAVID R. GLASS	Title	Date				
Conditions of approval, if any, are all a real Approval of its notice does not warrant or certify that						
the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office					
Title 18 U.S.C. Section 1001 and DUNCE Setting SE2, make it a crime for any correction						
Title 18 U.S.C. Section 1001 and DIANGE Section 322, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious						