NM OIL CONS COMMISSION Drawer DD

Artesia, NM 88210

- 1

Form	3160-5
(June	1990)

FORM APPROVED

01111 5100 5	TED STATES NT OF THE INTERIOR	Budget Bureau No. 1004-0135 Expires: March 31, 1993
BUREAU OF LAND MANAGEMENT		5. Lease Designation and Serial No. NM 80645
Do not use this form for proposals to de	AND REPORTS ON WELLS rill or to deepen or reentry to a different reservoir. PR PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
	T IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Well Well Other 2. Name of Operator	· · · · · · · · · · · · · · · · · · ·	8. Well Name and No. Lily ALY Federal #1
YATES PETROLEUM CORPORATION 3. Address and Telephone No.	(505) 748–1471)	9. API Well No. 30-015-27262
105 South 4th St., Artesia, 4. Location of Well (Footage, Sec., T., R., M., or Survey I	NM 88210 Description)	10. Field and Pool, or Exploratory Area Wildcat Delaware
660' FNL & 660' FEL, Section 3		11. County or Parish, State Eddy County, NM
12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPOF	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other Perforate & Treat	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Describe Proposed or Completed Operations (Clearly state give subsurface locations and measured and true vert	all pertinent details, and give pertinent dates, including estimated date of starting tical depths for all markers and zones pertinent to this work.)*	any proposed work. It well is directionally drilled

3-16-94. Drilled out DV tool at 6570'.

Perforated 8013-8165' w/17 - .42" holes (1 SPF) as follows: 8013, 14, 15, 16, 17, 18, 20, 21, 24 and 8025'; 8156, 59, 60, 62, 63, 64 and 8165'. Straddled perfs 8156-65' and acidized w/500 gals 7½% NEFE acid. Straddled perfs 8013-25' and acidized w/500 gals 7½% NEFE acid. 3-18-94. Frac'd perforations 8013-8165' w/94500 gals 35# X-link gel, 180,000# 16/30 Brady sand and 69,000 # 16/30 resin coated sand.

ARE ARE	E	
	22	:
		ľ
	c >	ŗ
	7	17
		C.
Ο.,	ည်	
	A La Caracteria de la C	AR 22 HOTAM

•		as in contrasting the contrasting to the contrastin
I hereby certify that the foregoing is true and correct Signed Amula and List	Tide Production Supervisor	Date 3-21-94
Approved byConditions of approval, if any:	Title	Date