Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED get Bureau No. 1004-0135	
ger Dureau 110. 1001-0155	

			J. vi. Oli C	<i></i>	~6
form 3160-5 June 1990)	DEPARTMENT	D STATES OF THE INTERIOR ND MANAGEMENT	37. C. 36.	10-2834	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 Lease Designation and Serial No.
Do not use this fo	SUNDRY NOTICES All orm for proposals to drill Jse "APPLICATION FOR I	or to deepen or reent	try to a different reser proposals	voir.	NM-80645 If Indian, Allottee or Tribe Name
	SUBMIT II	N TRIPLICATE	528 272 835	7.	If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Well Well	Other		↑	8.	Well Name and No.
2. Name of Operator	LEUM CORPORATION	(505)) 748-147EIVED	2) ω 9.	Lily ALY Federal #1 API Well No.
3. Address and Telephone	No.	00210	ARTESIA	57/10.	30-015-27262 Field and Pool, or Exploratory Area
105 South 4 4. Location of Well (Foota	th St., Artesia, NM ge, Sec., T., R., M., or Survey Desc 60' FEL of Section	ription)			Ingle Wells Delaware County or Parish, State
660' FNL & 6	60' FEL of Section	3-T24S-R31E (Uni	it A, NENE)		
					Eddy Co., NM
12. CHECK	APPROPRIATE BOX(s)	TO INDICATE NAT			OR OTHER DATA
TYPE OF	SUBMISSION		TYPE OF AC	CTION	<u></u>
Notice	of Intent	Abandoi Recomp			Change of Plans New Construction
X Subseq	uent Report	Pluggin	g Back		Non-Routine Fracturing Water Shut-Off
	Abandonment Notice	X Other	Casing Add perfs in Del acidize		Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)
give subsurface to 10-11-97 - and pump. 10-12-13-97 Rigged dowr 10-14-9742" holes Delaware). 2-7/8" tub:	Moved in and rigged Nippled up BOP. Since the Nippled up BOP. Since the Nippled up hot on hot oiler. TOOH with casing	depins for all markets and zon il up pulling uni- nut well in. iler. Pumped how with tubing and . TIH with 4" of 42, 43, 47, 48, guns and rigged 04' and tested to 7241-7258' with ealers. Swabbed	t. Pumped 30 bb t water and chem tubing anchor. casing gurs and p , 49, 50, 55, 56, down wireline. to 1500 psi. Pul n 1350 gallons 7-	ols 2% K nicals to Shut do perforate , 57 & 7 TIH with lled up -1/2% 11	to cut paraffin. own. ted 7241-7258' w/11 7258' (1 SPF - th RBP, packer and and set packer at con control HCL acid,
14. I hereby certify that (the foregoing is true and correct	Title Opera	itions Technician	!	Oct. 15, 1997
	ral or State office use)				Date
Approved by Conditions of approv	al, if any:	Tide			Date

ROSSELL OF HOE

150 ENVED