

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210
FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

c15F

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

JUN 15 '94

(505) 748-9471
C.D. OFFICE
ARTESIA

5. Lease Designation and Serial No.
NM-80645

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Lily ALY Federal #2

9. API Well No.
30-015-27263

10. Field and Pool, or Exploratory Area
Wildcat Delaware

11. County or Parish, State
Eddy Co., NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other Production Casing & cement

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8280'. Reached TD at 1:00 AM 5-15-94. Ran 202 joints of 5-1/2" 17# & 15.5# casing as follows: 33 joints of 5-1/2" 17# N-80 (1316.69'); 148 joints of 5-1/2" 15.5# J-55 (6097.29') and 21 joints of 5-1/2" 17# J-55 (866.95') (Total 8280.93') of casing-set at 8280'. Float shoe set at 8280'. Float collar set at 8242.17'. DV tool set at 6511.94'. Marker joint set at 7918.57'. Cemented in 2 stages as follows: Stage 1: 275 sacks Class "H", 8#/sack CSE, 5#/sack gilsonite, 6/10% CF-14 and .35% Thrifty-lite (yield 1.75, weight 13.6). Tailed in with 50 sacks "H", 10% Thixad and 8#/sack Hi-seal (yield 1.38, weight 15.5). PD 11:20 AM 5-16-94. Bumped plug to 650 psi for 1 minute. Circulated through DV tool for 2-3/4 hours. Stage 2: 500 sacks Pacesetter Lite "C" (65:35:6), 5#/sack gilsonite, 5#/sack salt and 6/10% CF-14 (yield 1.85, weight 12.6). Tailed in with 150 sacks Class H, 8#/sack CSE, 5#/sack gilsonite, 6/10% CF-14 and .35% Thrifty-lite (yield 1.75, weight 13.6). PD 3:30 PM 5-16-94. Bumped plug to 1250 psi for 1 minute. Tie back 500' inside intermediate casing on 2nd stage. WOC. Released rig at 7:30 PM 5-16-94.

Prep to move in completion unit.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date May 18, 1994

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

Date

JUN 13 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side