orm 3160-5 une 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 dsF

Expires: March 31, 1993

5. Lease Designation and Serial No.

	NM-80645	
6.	If Indian, Allottee or Tribe	Name

SUNDRY NOTICES AND REPORTS ON WELLS s to drill or to deepen or reentry to a different reservoir.

Do not use this form for proposals to drill of to de Use "APPLICATION FOR PERMIT	—" for such proposals RECEIVE	
		7. If Unit or CA, Agreement Designation
SUBMIT IN TRIP		
. Type of Well	JUN ~ 8 .	8. Well Name and No.
X Oil Gas Other		
Name of Operator	O. C. D	
YATES PETROLEUM CORPORATION	(505) 748-1474P) ESIA, OF	30-015-27265
3. Address and Telephone No.	0	10. Field and Pool, or Exploratory Area
105 South 4th St., Artesia, NM 8821	.0	Wildcat Delaware
Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL & 660' FEL of Section 3-T24	4S-R31E (Unit H, SENE)	11. County or Parish, State
	·	Eddy Co., NM
2. CHECK APPROPRIATE BOX(s) TO IN	IDICATE NATURE OF NOTICE, F	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF A	
	Abandonment	Change of Plans
☐ Notice of Intent	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
75) Scosedneur Kebou	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
Final Abandoliment Notice	X Other Intermediate cas	ing & Dispose Water (Note: Report results of multiple completion on
·	cement	Completion or Recompletion Report and Log lo
TD 4275'. Ran 105 joints of 8-5/8"	32# J-55 (4278.14') of cas	of starting any proposed work. If well is directionally design set at 4275'. 1-Texas 4235.28'. Cemented with 11 and (vield 2.01, weight 12.5
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C"	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar resumed drilling.	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 l.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled one to 11". Drilled plug and
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar	32# J-55 (4278.14') of cas 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield 1	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 L.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled on
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar resumed drilling.	32# J-55 (4278.14') of case 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield is, OK. Circulated 223 sach and 45 minutes. Reduced hold for the same of the sa	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 l.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled one to 11". Drilled plug and
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar resumed drilling.	32# J-55 (4278.14') of case 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield is, OK. Circulated 223 sach and 45 minutes. Reduced hold for the same of the sa	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 eal (yield 2.01, weight 12.5 l.32, weight 14.8). PD 4:50 ks to pit. WOC. Drilled one to 11". Drilled plug and
TD 4275'. Ran 105 joints of 8-5/8" Pattern notched guide shoe set at 4 sacks Pacesetter Lite "C", 10#/sack Tailed in with 200 sacks Class "C" AM 5-24-94. Bumped plug to 1500 ps at 8:45 AM 5-25-94. WOC 27 hours ar resumed drilling.	32# J-55 (4278.14') of case 275'. Float collar set at salt and 1/4#/sack cellose Neat with 2% CaCl2 (yield is, OK. Circulated 223 sach and 45 minutes. Reduced hold for the Production Clerk	sing set at 4275'. 1-Texas 4235.28'. Cemented with 11 2al (yield 2.01, weight 12.5 1.32, weight 14.8). PD 4:50 as to pit. WOC. Drilled on e to 11". Drilled plug and

or representations as to any matter within its jurisdiction.