

YATES PETROLEUM CORPORATION  
Lily ALY Federal #1  
Section 3-T24S-R31E  
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:


6-7-97 - Swabbed. Frac'd perforations 6683-6756' (via 2-7/8" tubing) with 17000 gallons 20# crosslink gel, 45000# 20-40 Ottawa sand and 12000# 16-30 Super LC sand. Shut well in.

6-8-97 - Released packer and TOOH with packer and tubing. TIH with retrieving tool and tubing. Tagged sand at 6750'. Washed 50' of sand. Released RBP and moved to 6642'. Set RBP and tested to 1500 psi. TOOH with tubing.

6-10-97 - Rigged up wireline. TIH with 4" casing guns and perforated 6590-6594' w/8 .42" holes (2 SPF). TOOH with casing guns. Rigged down wireline. TIH with packer and tubing. Set packer at 6481'. Acidized perforations 6590-6594' with 1000 gallons of 7-1/2% iron control HCL acid and ball sealers. Swabbed. Shut well in.

6-11-97 - Swabbed. Frac'd perforations 6590-6594' with 9550 gallons 20# crosslink gel, 20000# 20-40 Ottawa sand and 6000# 16-30 Super LC sand. Shut well in overnight.

6-12-97 - Blowed well down. Released packer. TOOH with tubing and packer. TIH with retrieving tool and tagged sand at 6600'. Washed 40' of sand off of RBP. Released RBP. TOOH with tubing and RBP. Released well to production department.



Rusty Klein  
Operations Technician  
June 13, 1997

RECEIVED

1997 JUN 17 A 9:24

BUREAU OF LAND MANAGEMENT  
ROSSELL OFFICE