YATES PETROLEUM CORPORATION Lily ALY Federal #5 Section 3-T24S-R31E Eddy County, New Mexico

## SUNDRY NOTICE CONTINUED:

4-1-97 - Swabbed. Released packer and TOOH. Rigged up wireline. TIH with 4" Select Fire guns and perforated 6666-6877' w/30 .42" holes as follows: 6666, 68, 75, 77, 84,85, 6752, 53, 54, 63, 64, 65, 74, 75, 76, 6849, 50, 51, 55, 59, 60, 61, 62, 65, 66, 70, 71, 72, 76 & 6877' (1 SPF - Cherry Canyon). TOOH with guns and rigged down wireline. TIH with packer and retrieving tool. Straddled perforations 6860-6877'. Acidized with 1000 gallons 7-1/2% iron control HCL acid and ball sealers. Moved tools. Straddled perforations 6763-6776'. Acidized with 1000 gallons 7-1/2% iron control HCL acid and ball sealers. Moved tools. Straddled perforations 6666-6685'. Acidized with 1000 gallons 7-1/2% iron control HCL acid and ball sealers. Moved tools. Straddled perforations 6763-6776'. Acidized with 1000 gallons 7-1/2% iron control HCL acid and ball sealers. Moved tools. Straddled perforations 6666-6685'. Acidized with 1000 gallons 7-1/2% iron control HCL acid and ball sealers. Moved tools. Tested RBP. Straddled perforations 6666-6877' and began swabbing.

Rustly Klefn

Operations Technician April 2, 1997