

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 990' FEL of Section 3-T24S-R31E (Unit I, NESE)

5. Lease Designation and Serial No.

NM-80645

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Lily ALY Federal #5

9. API Well No.

30-015-27275

10. Field and Pool, or Exploratory Area

Ingle Wells Delaware

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Frac perforations

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-2-97 - Swabbed. Shut well in.

4-3-97 - Swabbed. Frac'd perforations 6666-6877' (via 2-7/8" tubing) with 17000 gallons 20# crosslink gel, 45000# 20-40 Ottawa sand and 12000# 16-30 resin coated sand. Shut well in overnight.

4-4-97 - Nippled down frac head. Released packer and ran down hole. Tagged sand at 6815'. TOOH with packer. TIH with retrieving tool. Washed sand to RBP at 6944'. Released RBP. TOOH. TIH with production string. Set down with tailpipe at approx. 7050'. Anchor was not set. Picked up and tagged 2-3 times. TOOH.

4-5-97 - TIH with retrieving tool and tubing. Tagged at 6976'. Washed 25'. Fell thru. TIH to RBP at 7900'. Circulated clean. TOOH. TIH with production tubing. Nippled down BOP. Set tubing anchor at 6575' and seating nipple at 7450'. Released well to production department.

ACCEPTED FOR RECORD

APR 15 1997

BLM

RECEIVED

APR 11 1997

ROSWELL, NM

14. I hereby certify that the foregoing is true and correct

Signed

*Rusty Blair*

Title Operations Technician

Date April 9, 1997

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date