015 F

Form 3160-5 (June 1990) UNITED STATES

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

(1 = 1)	T OF THE INTERIOR LAND MANAGEMENT	Expires: March 31, 1993 5. Lease Designation and Serial No.
	AND REPORTS ON WELLS Il or to deepen or reentry to a different reservoir.	NM-82904 6. If Indian, Allottee or Tribe Name
	R PERMIT—" for such proposals	Not Applicable
SUBMI	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well		Not Applicable
Oil Gas Other	·	8. Well Name and No.
2. Name of Operator		Adeline ALN Federal #16
YATES PETROLEUM CORPORATION	(505) 748-1471)	9. API Well No.
3. Address and Telephone No.		30-015-27280
105 South 4th St., Artesia, N	NM 88210	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey 1)	escription) -	South Sand Dumes Delaware
660' FSL & 660' FEL, Unit P, 330	Section 6-T24S-R31E	11. County or Parish, State
		Eddy, New Mexico
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Spud, Set Surface Csg	-
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state a	Il pertinent details, and give pertinent dates, including estimated date of starting	g any proposed work. If well is directionally drilled,
_	cal depths for all markers and zones pertinent to this work.)*	
-	31-93 with rathole. Set 40' of 20" co	
to surface. Notified BLM, Carlsbad, NM, of spud. Resumed drilling $17-1/2$ " hole 6:30 PM $11-1-93$. Ran 13 joints $13-3/8$ " $54.5\#$ J-55 ST&C casing set 550'. Guide shoe set 550', insert		
float set 510'. Cemented with 275 sx PSL "C" + 2% CaCl2 + 1/4#/sx Celloseal (yield 1.89, wt		
12.7). Tailed in with 250 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 7:00 AM 11-2-93. Bumped plug to 500 psi, float held OK. Circulated 140 sacks cement. WOC. Drilled out at		
	rs. Reduced hole to 11" and resumed of	
	A property COT Set 1 (Fe 1) A Set 1	
<i>}</i>	ACCEPTE	
	n la kann navia r. ć	HA \$S
	Lames almost MEX	ico
	CARLSBAD, NEW MEX	
14. I hereby certify that the foregoing is true and correct		
Standelianila boli	Tide Production Supervisor	Date 11-8-93
(This space for Federal or State office use)		
Approved by	Title	Date