
UNITED STATES FORM APPROVED une 1990) Budget Bureau No. 1004-0135 DEPARTMENT OF THE INTERIOR Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT NM-82904 SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOF PERMIT-" for such proposals SUBMIT IN TRIPLICATE I. Type of Well

5. Lease Designation and Serial No. 6. If Indian, Allottee or Tribe Name Not Applicable 7. If Unit or CA, Agreement Designation Not Applicable Oil Well 8. Well Name and No. 2. Name of Operator Adeline ALN Federal #16 YATES PETROLEUM CORPORATION (505) 748-1471)9. API Well No. 3. Address and Telephone No. 30-015-27280 105 South 4th St., Artesia, NM 88210 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) South Sand Dumes Delaware 660' FSL & 660' FEL, Unit P, Section 6-T24S-R31E 11. County or Parish, State Eddy, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Intermediate Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled,

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-7-93. Ran 91 joints 8-5/8" 32# J-55 casing set 4087'. Float shoe set 4087', float collar set 4042'. Cemented with 1450 sx PSL "C" w/10#/sx salt, 1/4#/sx Celloseal (yield 2.01, wt 12.5). Tailed in with 200 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 9:35 PM 11-7-93. Bumped plug to 1750 psi, flcat held okay. Circulated 280 sacks cement. WOC. Drilled out 10:00 PM 11-8-93. WOC 24 hours and 25 minutes. NU and tested to 1000 psi for 15 minutes. Reduced hole to 7-7/8" and resumed drilling.



	CARLSBAD, NEW M	IEXICO
nereby certify that the foregoing is true and correct	Tide Production Supervisor	Date 11-10-93
proved by	Title	Date
18 U.S.C. Section 1001, makes it a crime for any person kno	wingly and willfully to make to any department or agency of the Unite	ed States any false, fictitious or fraudulent stater