


YATES PETROLEUM CORPORATION  
Adeline ALN Federal #15  
Section 6-T24S-R31E  
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

10-10-2000 - Bled well down. Swabbed. Shut well in.  
10-11-2000 - Bled well down. Swabbed. Released packer and TIH and released RBP.  
Moved RBP to 6750' and packer to 6690'.  
10-12-2000 - Tested RBP to 1500 psi, OK. Released packer and TOOH. Rigged up wireline.  
TIH with 4" casing guns and perforated 6608-6622' w/8 .42" holes as follows: 6608, 09,  
10, 18, 19, 20, 21 & 6622' (1 SPF - Delaware). TOOH with casing guns and rigged down  
wireline. TIH with packer to 6540'. Shut well in.  
10-13-2000 - Acidized perforations 6608-6622' with 1000 gallons 7-1/2% iron control HCL  
acid and ball sealers. Swabbed. Shut well in.  
10-14-16-2000 - Swabbed. Shut well in.  
10-17-2000 - Swabbed. Shut well in.  
10-18-19-2000 - Shut in. Prep to frac.  
10-20-2000 - Bled well down. Frac'd perforations 6608-6622' with 11370 gallons 40#  
crosslink gel, 17500# 20-40 Super LC sand and 6250# 16-30 Super LC sand. Rigged up  
for forced closure. Shut well in. Opened well and began flowing back frac.  
10-21-23-2000 - Released packer and TOOH. TIH with RBP retrieving tool and sand bailer.  
Bailed 78' of sand. Latch onto and released RBP. TOOH with bailer and RBP. TIH with  
production tubing as follows: bull plug at 7949', 6 joints 2-7/8" tubing, Cavins tool,  
4' sub, seating nipple at 7736', 38 joints of tubing, 5-1/2" tubing anchor at 6540' and  
208 joints of 2-7/8" tubing. Shut well in. Released well to production department.

Open perforations: 6608-8021' (Delaware)

  
\_\_\_\_\_  
Rusty Klein  
Operations Technician  
October 30, 2000