

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION ✓

3. Address and Telephone No.

105 South Fourth Street, Artesia, New Mexico 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter I; 1980' FSL and 660' FEL
Section 33-T25S-R29E
Eddy County, New Mexico

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-77021

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Corral Federal Unit #1

8. Well Name and No.

9. API Well No.

30-015-27522

10. Field and Pool, or Exploratory Area

Wildcat Delaware

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☒ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Yates Petroleum Corporation wishes to change the casing program to surface casing of 9 5/8", 36#, J-55, ST & C casing set at 450' in a 14 3/4" hole. Circulate cement to surface with 400 sx Lite and 200 sx "C" with 2% CaCl₂. No intermediate casing. Drill out with 8 3/4" bit to new TD of 5700' (a change from 6950'). Run 5 1/2", 15.5#, J-55, LT & C casing to TD and cement in two stages with DV tool at 4500'. (Circ. Cmt.)

1st Stage: Cement with 250 sx "C". 2nd Stage: Cement with 600 sx Lite and tail in 200 sx "C".

14. I hereby certify that the foregoing is true and correct

Signed

Clayton R. May

Title PERMIT AGENT

Date 4/8/94

(This space for Federal or State office use)

Approved by Orig. Signed by Shannon J. Shaw

Title

PETROLEUM ENGINEER

Date 4/8/94

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side