

clsf

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
 Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED
 Budget Bureau No. 1004-0135
 Expires: March 31, 1993

5. Lease Designation and Serial No.
 NM 77021

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
 Corral Federal Unit #1

9. API Well No.
 30-015-27522

10. Field and Pool, or Exploratory Area
 Wildcat Delaware

11. County or Parish, State
 Eddy, NM

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other Plugged & Abandoned Well

2. Name of Operator
 YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.
 105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
 1980' FSL & 660' FEL, Section 33-T25S-R29E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☐ Other

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5-3-94. TD 5825'. Reached TD 5-1-94. Plugged well as follows:

- Plug #1) 5721-5571' - Cemented with 65 sx Class "C" Neat. Laid down 92 joints drill pipe.
- Plug #2) 2842-2742' - Cemented with 105 sx Class "C" Neat. Laid down 62 joints drill pipe.
- Plug #3) 815-665' - Cemented with 150 sx Class "C" Neat with 2.8% CaCl₂. TOH with 3 stands. WOC 2-1/2 hours. TIH and tagged plug at 642'. Laid down 25 joints drill pipe (50' inside 9-5/8" and 100' outside 9-5/8" casing).
- Plug #4) 50-0' - Cemented with 17 sx Class "C" Neat. Laid down 2 joints drill pipe.

Rigged down Western. Set Regulation abandonment marker. Well plugged and abandoned 5-3-94.

Part ID-2
 6-24-94
 P & A

Approved as to plugging of the well bore
 liability under bond is retained until
 surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Production Supervisor

Date 5-9-94

(This space for Federal or State office use)

Approved by (ORIG. SGD.) JOE G. LARA

Title PETROLEUM ENGINEER

Date 5/31/94

Conditions of approval, if any: