

District I  
1625 N. French Dr., Hobbs, NM 87240

District II  
811 South First, Artesia, NM 87210

District III  
1000 Rio Brazos Rd., Aztec, NM 87410

District IV  
2040 South Pacheco, Santa Fe, NM 87505

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

WELL API NO. 30-015-27713

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Delta "9" Fee

8. Well No. 1

9. Pool name or Wildcat  
Wildcat (Delaware)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator Devon SFS Operating, Inc.

3. Address of Operator 20 N. Broadway, Suite 1500  
Oklahoma City, OK 73102-8260

4. Well Location

Unit Letter M : 660 feet from the South line and 660 feet from the West line

Section 9 Township 25S Range 28E NMPM County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
GR=2993' KB=3010'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.

Devon Proposes To Permanently Plug And Abandon As Follows:

1. Set CIBP at 6,000' and cap with 35' cement.
2. Cut off 5 1/2" casing at 2,530' (base of salt at 2,482'). POOH with casing and LD.
3. Spot balanced cement plug 2,430'-2,580'. WOC. Tag plug.
4. Spot a balanced cement plug 910'-1,010' (top of salt at 960'). WOC. Tag plug.
5. Spot balanced cement plug 360'-460' (surface casing shoe at 412'). WOC. Tag plug.
6. Spot cement plug 0'-~~20~~ 60'.
7. Cut off 8 5/8" casing 3' below ground level and install dry hole marker.
8. Restore location.

25 sx plug @ 5075

Note: Cement to be Class "C" at 14.8 ppg with a yield of 1.32 cu ft/sx.  
9.5 ppg mud shall be spotted between cement plugs.

Notify OCD 24 hrs. prior to any work done

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Charles H. Carleton TITLE Senior Engineering Technician DATE 05/13/2002

Type or print name Charles H. Carleton Telephone No. (405)552-4528

(This space for State use)

APPROVED BY [Signature] TITLE Wild Sep ID DATE MAY 30 2002

Conditions of approval, if any: