

Enron Oil & Gas Company
Gunnison 34 Federal, Well No. 1
1880' FSL & 2180' FEL
Sec. 34, T25S, R31E
Eddy County, New Mexico

6. Types and Characteristics of the Proposed Mud System:

The well will be drilled to TD with a combination of brine, cut brine, and polymer/KCl mud system. The applicable depths and properties of this system are as follows:

<u>Depth</u>	<u>Type</u>	<u>Weight (ppg)</u>	<u>Viscosity (sec)</u>	<u>Waterloss (cc)</u>
0 - 600'	Fresh water (spud)	8.5	40-45	N.C.
600' - 4230'	Brine water	10.0	30	N.C.
4230' - TD	Cut Brine & polymer/KCL	8.8-9.2	28	N.C.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

7. Auxiliary Well Control and Monitoring Equipment:

- (A) A kelly cock will be kept in the drill string at all times.
- (B) A full opening drill pipe stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- (C) A mud logging unit will be continuously monitoring drilling penetration rate and hydrocarbon shows from 3900' to TD.