

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

Form approved.  
Budget Bureau No. 1004-0137  
Expires August 31, 1985

Other instructions on reverse side

RECEIVED  
JUL 11 9 41 AM '94  
BUREAU OF LAND MANAGEMENT  
ALBUQUERQUE, NM 88210

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL: OIL WELL  GAS WELL  DRY  Other   
 b. TYPE OF COMPLETION: NEW WELL  WORK OVER  DEEP-EN  PLUG BACK  DIFF. RENVR.  Other

2. NAME OF OPERATOR: Fortson Oil Company  
 3. ADDRESS OF OPERATOR: 301 Commerce St., Suite 3301, Ft. Worth, TX 76102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)\*  
 At surface: 2310' FNL & 1980' FEL  
 At top prod. interval reported below: Same  
 At total depth: Same

14. PERMIT NO. \_\_\_\_\_ DATE ISSUED \_\_\_\_\_

5. PHASE DESIGNATION AND SERIAL NO.: LC-061705-B  
 6. IF INDIAN, ALLOTTEE OR TRIBE NAME \_\_\_\_\_  
 7. UNIT AGREEMENT NAME \_\_\_\_\_  
 8. FARM OR LEASE NAME: Poker Lake Unit  
 9. WELL NO.: 89  
 10. FIELD AND POOL, OR WILDCAT: Poker Lake Delaware  
 11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: Sec. 25, T24S, R30E  
 12. COUNTY OR PARISH: Eddy  
 13. STATE: NM

15. DATE SPUDDED: 2/25/94  
 16. DATE T.D. REACHED: 3/13/94  
 17. DATE COMPL. (Ready to prod.): 6/06/94  
 18. ELEVATIONS (DF, RKB, RT, GR, ETC.): 3435' GL; 3447' KB  
 19. ELEV. CASINGHEAD \_\_\_\_\_

20. TOTAL DEPTH, MD & TVD: 8150'  
 21. PLUG, BACK T.D., MD & TVD: 7998'  
 22. IF MULTIPLE COMPL., HOW MANY? \_\_\_\_\_  
 23. INTERVALS DRILLED BY: All  
 ROTARY TOOLS: \_\_\_\_\_ CABLE TOOLS: \_\_\_\_\_

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)\*: 6670-6769' Delaware  
 25. WAS DIRECTIONAL SURVEY MADE: No

26. TYPE ELECTRIC AND OTHER LOGS RUN: CNL/LDT/GR/CAL SJS  
 27. WAS WELL CORRED: Yes

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	48#, H-40	720	17-1/2"	350 sx C1 C+300 sx C1 C	
8-5/8"	32#, J-55	4080	11"	150 sx 65:35 Pox+300 sc C	C
5-1/2"	17#&15.5#, J-55	8150	7-7/8"	650 sx C1 H+180 sx C1 H+	
				200 sx C1 H	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)

31. PREPARATION RECORD (Interval, size and number)

7930-40', .4", 40 holes  
 7848-57' & 65', .4", 12 holes  
 7789-92', 7799-7808', .4", 12 holes  
 6670-6769, .4", 14 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
7930-40'	1500 gals 7.5% Pental 100 acid
7930-40'	Frac w/63,700# 16/30 sd
6670-6769'	Frac w/61,000# 16/30 sd

33. PRODUCTION

DATE FIRST PRODUCTION: 06/02/94  
 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump): Pumping  
 WELL STATUS (Producing or shut-in): Producing

DATE OF TEST	HOURS TESTED	CHOKER SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
07/01/94	24			400	375	180	938

FLOW. TUBING PRBL.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
			400	375	180	42

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.): Sold  
 TEST WITNESSED BY: SJS

35. LIST OF ATTACHMENTS: 8 1994

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED: [Signature] TITLE: Sr. Production Technician DATE: 07/06/94

\*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Bell Canyon	4208	5077	Sand & shale; water	Rustler	920'	920'
Cherry Canyon	5078	6687	Sand, shale & some lime; water	Base Salt	3960'	3960'
Brushy Canyon	6688	7761	Sand, shale; water	Lamar	4161'	4161'
Bushul Brushy Canyon	7762	7982	Sand, shale & lime; oil & water	Bell Canyon	4208'	4208'
				Cherry Canyon	5078'	5078'
				Brushy Canyon	6688'	6688'
				Bone Springs	8054'	8054'

38. GEOLOGIC MARKERS