

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CONSERVATION DIV  
811 S. 1st ST.  
ARTESIA, NM 88210-2894  
APPROVED

BLM - CRA

February 08, 1996

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir

Use "APPLICATION FOR PERMIT" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well

☐ Gas Well

☐ Other

2. Name of Operator

Bass Enterprises Production Company

3. Address and Telephone No.

P. O. Box 2760

Midland, Texas 79702-2760

(915) 683-2277

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FEL & 1980' FNL

Section 24, T24S-R30E

5. Lease Designation and Serial No.

NM-030453

6. If Indian, Allottee or Tribe Name

---

7. If Unit or CA, Agreement Designation

Poker Lake Unit

8. Well Name and No.

Poker Lake Unit #93

9. API Well No.

30-015-27798

10. Field and Pool, or Exploratory Area

Poker Lake (Delaware)

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

T.D., 5-1/2" casing, cement,  
Release Rig

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7-7/8" hole to 8199' 5/21/96.

Ran 193 joints 5-1/2" 17# & 15.50#, K-55 LT&C casing set @ 8199'.

Cemented in two stages:

Stage 1: Cement with 315 sx Class "H" cement with additives. Circ 115 sx to reserve pit off DV Tool @ 6377'

Stage 2: Cement with 375 sx 35/65 PozC with additives. Tail with 150 sx Class "C" neat.

T. O. C. @ 3470' by temperature survey. Released rig @ 3:00 a.m. on 5/21/96.

Prep for Completion.

14. I hereby certify that the foregoing is true and correct

Signed Tami L. Wilber Tami L. Wilber

Title Production Clerk

Date 5/31/96

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

Conditions of approval, if any: \_\_\_\_\_