

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

BLM - CRA

February 08, 1996

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals

5. Lease Designation and Serial No.

NM-030453

6. Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Poker Lake Unit

8. Well Name and No.

Poker Lake Unit #93

9. API Well No.

30-015-27798

10. Field and Pool, or Exploratory Area

Poker Lake (Delaware) SW

11. County or Parish, State

Eddy County, New Mexico

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well

☐ Gas Well

☐ Other

2. Name of Operator

Bass Enterprises Production Company

3. Address and Telephone No.

P. O. Box 2760

Midland, Texas 79702-2760

(915) 683-2277

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FEL, Unit Letter H

Section 24, T24S-R30E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

Add Perfs & Frac

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Set CIBP @ 7650'. 11/13/96

RIH with 4" casing gun loaded w/ 2 JSPF @ 180 degree phasing with GOEX 19 gram charges and perforate the following interval:
6856-66' (10', 20 shots)

Acidize with 800 gals 15% HCl acid with additives.

Frac with 5582 gals of Dowell Guar-based 30# gel XL with Borate and 6432# 20/40 RC sand. 11/15/96


RIH with 4" gamma gun loaded w/ 2 JSPF @ 120 degree phasing with GOEX 19 gram charges and perforate the following interval:
6863-73' (10', 20 shots)

Acidize with 1000 gals 7-1/2% HCl acid with additives and drop 60 1.3 spg ball sealers.

Frac with 6897 gals of YF-130 and 23,500# 20/40 RC sand. 11/8/96

Respace 2-1/2" x 1-1/2" x 24' RHBC pump

Return well to production. Producing interval: 6856-66', 6863-6873'. 12/13/96



RECEIVED

MAR 04 '97

BLM
ROSWELL, NM

Certified P960132469

14. I hereby certify that the foregoing is true and correct

Signed Tami L. Wilber Tami L. Wilber

Title Production Clerk

Date 2/26/97

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any: