

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

dist
up

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 83210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

AUG 15 1995

WELL API NO.
30-015-27895

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
E2206

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name
POKER LAKE UNIT

1. Type of Well:
OIL WELL GAS WELL OTHER

8. Well No.
105

2. Name of Operator
BASS ENTERPRISES PRODUCTION CO.

9. Pool name or Wildcat
POKER LAKE (DELAWARE) SW

3. Address of Operator
P.O. BOX 2760, MIDLAND, TX 79702-2760

4. Well Location
Unit Letter B : 660 Feet From The NORTH Line and 1980 Feet From The EAST Line
Section 36 Township 24S Range 30E NMPM EDDY County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3460' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: SPUD DATE & SURFACE CSG <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SPUD 14 3/4" HOLE 8-8-95
DRILLED 14 3/4" HOLE TO 690' 8-9-95.
RAN 16 JTS. 11 3/4" 42# WC-40 ST&C CSG. SET @ 690'.
CEMENTED WITH 200 SX CLASS "C" CEMENT WITH ADDITIVES
TAIL WITH 240 SX CLASS "C" WITH ADDITIVES, CEMENT DID NOT CIRCULATE
RAN TEMP. SURVEY T.O.C. @ 37' FROM SURFACE.
RAN 1" PIPE & MIX 98 SX CALSS "C" CEMENT WITH ADDITIVES
TOP OUT & CIRCULATE 13 SX TO SURFACE.
W.O.C. 14 HRS. TEST BLIND RAMS & MANIFOLD TO 200# & 1000 PSI, OK.
DRILL CEMENT & TEST CSG. TO 600 PSI, OK. DRILLING 11" HOLE 8-10-95.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE R.C. Houtchens R.C. HOUTCHENS TITLE SENIOR PRODUCTION CLERK DATE 8-14-95
TYPE OR PRINT NAME R.C. HOUTCHENS TELEPHONE NO. 915-683-2277

(This space for State Use)
ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR
APPROVED BY _____ TITLE _____ DATE AUG 17 1995
CONDITIONS OF APPROVAL, IF ANY: