

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

(See other in-  
structions on  
reverse side)FORM APPROVED  
OMB NO. 1004-0137  
Expires: February 28, 1995

## WELL COMPLETION OR RECOMPLETION REPORT AND LOG\*

1a. TYPE OF WELL: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> Other _____		5. LEASE DESIGNATION AND SERIAL NO. LC 061705 A	
b. TYPE OF COMPLETION: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEP-EN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR. <input type="checkbox"/> Other _____		6. IF INDIAN, ALLOTTEE OR TRIBE NAME . . .	
2. NAME OF OPERATOR Bass Enterprises Production Co.		7. UNIT AGREEMENT NAME Poker Lake Unit	
3. ADDRESS AND TELEPHONE NO. P.O. Box 2760 Midland, TX 79702-2760 (915) 683-2277		8. FARM OR LEASE NAME, WELL NO. Poker Lake Unit #106	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1980' FWL & 1980' FSL At top prod. interval reported below Same At total depth Same		9. API WELL NO. 30-015-27920	
14. PERMIT NO. _____ DATE ISSUED _____		10. FIELD AND POOL, OR WILDCAT Poker Lake (Delaware)	
15. DATE SPUDDED 4/24/97		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 25, T24S-R30E	
16. DATE T.D. REACHED 5/13/97		12. COUNTY OR PARISH Eddy	
17. DATE COMPL. (Ready to prod.) 6/12/97		13. STATE New Mexico	
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 3440.7 GL, 3457.3 KB		19. ELEV. CASINGHEAD . . .	
20. TOTAL DEPTH, MD & TVD 8138'		21. PLUG, BACK T.D., MD & TVD	
22. IF MULTIPLE COMPL., HOW MANY* Single		23. INTERVALS DRILLED BY →	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)* 7910-20'		25. WAS DIRECTIONAL SURVEY MADE No	
26. TYPE ELECTRIC AND OTHER LOGS RUN LD-CN-GR, AIGR		27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
11-3/4"	42#	804'	14-3/4"
8-5/8"	28#, 32#	4161'	11"
5-1/2"	15.5#, 17#	8138'	7-7/8"
29. LINER RECORD		30. TUBING RECORD	
SIZE	TOP (MD)	BOTTOM (MD)	PACKER SET (MD)
NA			
31. PERFORATION RECORD (Interval, size and number) 7910-20' - Perf w/ 4" casing gun loaded with 2 JSPF at 180 degree phasing (10', 20 shots)		32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. DEPTH INTERVAL (MD) 7910-20' AMOUNT AND KIND OF MATERIAL USED Frac with 38,910 gals YF130 gel + 182,228# 20/40 Brady sand and 11,000# Resin Coated Sand	
33.* PRODUCTION			
DATE FIRST PRODUCTION 6/13/97	PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump) Pumping, 2-1/2" x 1-1/2" x 24' RHBC		WELL STATUS (Producing or shut-in) Producing
DATE OF TEST 6/15/97	HOURS TESTED 24 hours	CHOKE SIZE NA	PROD'N. FOR TEST PERIOD →
FLOW. TUBING PRESS. - -	CASING PRESSURE - -	CALCULATED 24-HOUR RATE →	OIL - BBL. 89
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Sales, Lease Use		GAS - MCF. 184	WATER - BBL. 309
35. LIST OF ATTACHMENTS C-104, logs, inclination report		OIL GRAVITY - API (CORR.) 39.2	TEST WITNESSED BY
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records			
SIGNED <u>Dani L. Wilbur</u>		TITLE <u>Production Clerk</u>	
		DATE <u>7/11/97</u>	

\*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof perforated intervals and all drill-stem tests including depth intervals tested, pushion used, time to open, flowing and shut-in pressures and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
				T/Rustler	493'	493'
				T/Salt	878'	878'
				B/Salt	3896'	3896'
				T/Lamar Lime	4112'	4112'
				T/Ramsey Sand	4143'	4143'
				T/Cherry Canyon	6236'	6236'
				T/Livingston Ridg	6639'	6639'
				T/Lwr Brush Cany	7725'	7725'
				T/Bone Spring	8015'	8015'