

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

BLM - CRA

February 08, 1996

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well

☐ Gas Well

☐ Other

2. Name of Operator

Bass Enterprises Production Company

3. Address and Telephone No.

P. O. Box 2760

Midland, Texas 79702-2760

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 1980' FEL

Section 24, T24S-R30E, Unit Letter O

5. Lease Designation and Serial No.

NM-030453

6. If Indian, Allottee or Tribe Name

—

7. If Unit or CA, Agreement Designation

Poker Lake Unit

8. Well Name and No.

Poker Lake Unit #100

9. API Well No.

30-015-27961

10. Field and Pool, or Exploratory Area

Poker Lake (Delaware) SW

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

Add Perfs and Frac

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Set EZ drill BP @ 7000', test to 3000 psi, ok. 3/9/98

Spot 1500 gals 15% HCl acid across future perfs.

RIH w/ 4" casing gun loaded w/ 1 JSPF with 19 gram GOEX charges and 0 degree phased and perf the following interval:

6626-30' (4', 5 holes)

6682-86' (4', 5 holes)

6802-06' (4', 5 holes)

Frac with 32,294 gals SFG-2500 + 143,300# 16/30 Brady Sand

Set EZ drill BP @ 6200', test to 3000 psi, ok 3/12/98

RIH w/ 4" casing gun loaded with 2 JSPF with 19 gram GOEX charges and 0 degree phased and perf the following interval:

5804-08' (4', 8 holes)

5902-06' (4', 8 holes)

Frac with 23,486 gals SFG-2500 + 136,462# 16/30 Resin Coated Sand.

Tag top of sand @ 5986', wash sand to PBTD @ 6200'.

Return well to production.

Drill out EZ drill BP's @ 6200' & 7000' 3/24/98

Clean out sand fill to PBTD @ 8073'.

Return well to production.

ACCEPTED FOR RECORD
PETER W. CHESTER

JAN 12 1996

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

14. I hereby certify that the foregoing is true and correct

Signed

Tami Wilber

Tami Wilber

Title

Production Clerk

Date

12/8/98

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

CEIVED

SEP 10 1988

ROSWELL
BLM
NEW