

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different well.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

JUL 15 '94

Type of Well

☒ Oil ☐ Gas ☐ Other

O. C. D.

Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

Address and Telephone No.

105 South 4th St., Artesia, NM 88210

Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1980' FEL of Section 24-T24S-R31E (Unit G, SWNE)

Drawer DD
Artesia, NM 88210

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-57274

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Haracz AMO Federal #6

9. API Well No.

30-015-27972

10. Field and Pool, or Exploratory Area

Cotton Draw Brushy Canyon

11. County or Parish, State

Eddy Co., NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Intermediate casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4465'. Ran 110 joints of 8-5/8" 32# casing as follows: 8 joints of 8-5/8" 32# HC-80 (329.53') and 102 joints of 8-5/8" 32# K-55 ST&C (4156.60') (Total 4486.13') of casing set at 4465'. Float shoe set at 4465'. Float collar set at 4422.35'. Cemented with 1350 sacks Pacesetter Lite, 10#/sack salt and 1/4#/sack celloseal (yield 2.01, weight 12.5). Tailed in with 200 sacks Class "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 6:30 AM 7-4-94. Bumped plug to 1500 psi, OK. Circulated 120 sacks. Drilled out at 12:30 AM 7-5-94. WOC 18 hours. Nippled up and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling. NOTE: Installed 6 centralizers on alternate joints. Preceded cement with 15 bbls water.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date July 6, 1994

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side