

0512

Form 3160-5
 (June 1990)

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
 Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135
 Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-55142

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sterling Silver
 "3" Federal #4

9. API Well No.

30-015-28283

10. Field and Pool, or exploratory Area

Ingle Wells
 (Delaware)

11. County or Parish, State

Eddy Co., NM

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Santa Fe Energy Resources, Inc.

3. Address and Telephone No.

550 W. Texas, Suite 1330, Midland, TX 79701 915/687-3551

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

(M), 660' FSL and 710' FWL, Sec. 3, T-24S, R-31E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Ran casing string

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

02/25/95:

Depth 4191'. TD 11" hole at 5:00 a.m. MST. RU casing crew and ran 93 jts 8-5/8" 32.0# J-55 ST&C casing and set at 4188', FC @ 4098'. Cemented w/ 1200 sx C-Lite (35:65:6) containing 9 pps salt and 1/4 pps Cello-seal. Tail w/ 200 sx C1 "C" + 2% CaCl2. Plug down at 5:40 p.m. MST. Circ'd 150 sx cmt to pit. WOC.

02/26/95:

WOC. ND Hydril. Cut casing off and weld on head. NU BOP, Hydril, and kill manifold. Test blind rams to 1500 psi, ok. TIH w/ bit. Test pipe rams to 1500 psi, Hydril to 1500 psi, ok. WOC total of 24 hours. Resume drilling operations.



14. I hereby certify that the foregoing is true and correct.

Signed

Gerry McCullough

Title Sr. Production Clerk

Date 02/28/95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side