

PAGE START DATE: 5/30/97
 PAGE START TIME: 19:36: 0
 DATA FILE: 3

DELTA TIME HRS	DEPTH FEET	TEMPERATURE 'F	COMMENTS
0.000	4000.00	93.75	
0.450	5540.00	103.50	
0.500	5727.00	117.00	BREAK
0.525	5826.00	116.50	
0.550	5928.00	119.50	
0.567	5995.00	118.75	
0.575	6029.00	120.00	
0.583	6063.00	119.00	
0.608	6166.00	122.75	
0.617	6200.00	121.00	
0.642	6305.00	124.00	
0.650	6341.00	121.50	
0.667	6412.00	123.00	
0.700	6555.00	121.75	
0.708	6590.00	124.25	
0.717	6626.00	123.50	
0.725	6662.00	124.75	
0.733	6699.00	123.25	
0.742	6735.00	125.00	
0.750	6771.00	123.25	
0.775	6881.00	125.75	
0.800	6991.00	124.50	
0.808	7028.00	127.00	
0.817	7066.00	124.75	
0.833	7115.00	128.25	M.D.R.

DATE AND TIME CEMENT JOB COMPLETE:

MAY 30, 1997 @ 11:15 AM

DATE AND TIME SURVEY MADE:

MAY 30, 1997 @ 8:00 PM

AMOUNT AND TYPE CEMENT USED:

160 SACKS CLASS "H" WITH ADDITIVES;
 SECOND STAGE 225 SACKS PLUS ADDITIVES,
 RUN THROUGH DV TOOL @ 7125 FEET,
 BEHIND 5½" CASING IN A 7-7/8" HOLE.

DEPTH FIGURED FROM:

KELLY BUSHING