

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P. O. Box 1980, Hobbs, NM 88240

DISTRICT II

811 S. 1st Street, Artesia, NM 88210-2834

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P. O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-29460

5. Indicate Type of Lease

State ☒ Fee ☐

6. State Oil & Gas Lease No.

001796

7. Lease Name or Unit Agreement Name

Poker Lake Unit

8. Well No

127

9. Pool Name or Wildcat

Corral Canyon (Delaware) NE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Bass Enterprises Production Company

3. Address of Operator

P. O. Box 2760 Midland, Texas 79702-2760

4. Well Location

Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line
Section 2 Township 25S Range 30E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3331' GL, 3348.5' RKB

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Drill to TD, Log & Plug and Abandon Procedure ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 7992'. 4/13/97-4/18/97.

Ran Logs. Go in hole open ended with drill pipe circulated and cond. hole set plugs as follows:

Ken Livingstone with NMOCD contacted regarding plugging procedure @ 11:40 a.m. on 4/22/97

Plug #1 set @ 6500-6755' with 100 sx Class H cement with additives. Circulate. Tag cement at 6488'.

Plug #2 set @ 5600-6200' with 260 sx Class H cement with additives. Cement was mixed in error @ 8.2 gal/sx instead of 5.2 gal/sx.

Plug is 600' instead of 300'. Circulate.

Plug #3 set @ 3850-4100' with 100 sx Class "C" neat with additives.

Plug #4 set @ 0-185' with 100 sx Class "C" neat with additives.

Rig released @ 2:00 p.m. on 4/23/97. Wellhead cut off and dry hole marker installed 4/26/97. Fence reserve pit and cellar.

Well is plug and abandoned. Final Report.

Post ID-2
6-6-97
P4A

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Tami L. Wilber

TITLE:

Production Clerk

DATE:

5/1/97

TYPE OR PRINT NAME

Tami L. Wilber

Telephone No. (915) 683-2277

(This space for State Use)

APPROVED BY:

Michael C. Sheffield

TITLE:

Field Rep. II

DATE:

6-22-97

CONDITIONS OF APPROVAL, IF ANY: