Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135 Expires: March 31, 1993

N.M. Oil Cons. Division NM-18626 SUNDRY NOTICES AND REPORTS ON WESIS S. 1st Street 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals, NM 88210-2834 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. ⊠ Oil Well Other Amoco Federal #1 2. Name of Operator 9 API Well No. SDX Resources, Inc. 30-015-29462 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area PO Box 5061, Midland, TX 79704 915/685-1761 Ross Draw, Delaware, E. 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 660' FSL & 660' FEL 11. County or Parish, State Sec. 24, T26S, R30E, Unit P Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent New Construction Recompletion Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Dispose Water Other (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work.)* **Existing Condition:** 13-3/8" @ 504'. Cmt w/475 sx, circ. 8-5/8" @ 3505'. Cmt w/1500 sx Lite & 300 sx Cl C, circ. 5-1/2" @ 6804'. 2 stage cmt. DV tool @ 5523'. Stage 1: 325 sx 50/50 POZ H, circ. Stage 2: 750 sx POZ H. TOC 3475' by CBL. Perfs: 6208-6276' w/CIBP @ 6125' Perfs: 5849-59' Propose to P&A as follows: Circ hole w/mud laden fluid. Spot 25 sx plug @ 5860 - 5610' TAG - per O. (. D. - Mike S. Cut 5-1/2" csg @ 3475 & pull. Spot 25 sx plug 3575 - 3418' TAG Spot 30 sx plug 1460 - 1360' Spot 30 sx plug 500 - 400' Spot 10 sx surface plug & install marker. Clean, rip & re-seed location & access road. 14. I hereby, cartify that the foregoing 02/14/01 Regulatory Tech PETROLEUM ENGINEER Federal or State office use)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(ORIG. SGD.) GARY GOURLEY

Conditions of approval, if any: