

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-015-29560

Indicate Type of Lease

STATE ☒

FEE ☐

State Oil & Gas Lease No.

Lease Name or Unit Agreement Name

Cottonwood "36" State

Well No.

1

Pool name or Wildcat

Cottonwood Draw - Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

Name of Operator
Penwell Energy, Inc.

Address of Operator
600 N. Marienfeld, Suite 1100, Midland, TX 79701

Well Location

Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line

Section 36 Township 25S Range 26E NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.)

3322' GR

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ANBANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

COTTONWOOD "36" STATE #1

1. Run tubing to 5400'.
2. Load Hole with 150 bbls. gelled brine.
3. Spot 25 sx. cement 5175' - 5400' across perms 5386' - 5396'. WOC. Tag Plug.
4. Spot 25 sx. cement 2075' - 2300'. * T.O.C. 3100' Perforate + squeeze.
100 cmt plug inside & outside 5 1/2" csg.
5. Cut 5 1/2" csg @ 1900'.
1950'
6. Spot 120 sx. cement 1510' - 1925'. WOC. Tag plug. * T.SALT 200' 30sx cement Plug
800' - 700' TAG
7. Spot 30 sx. cement 300' - 400'. WOC. Tag plug.
8. Spot 5 sx. cement 3' - 10'. * lost surface plug.
9. Cut off wellhead. Cap w/1/4" steel plate.

* Notify NM OGD to witness Plugging Operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Russell L. Corlett TITLE Engineer

DATE 07-29-98

TYPE OR PRINT NAME RUSSELL L. CORLETT

TELEPHONE NO. 915-683-2534

(This space for State Use)

APPROVED BY Marie S. Turbellefield TITLE Field Rep. II

DATE Aug. 4-98

CONDITIONS OF APPROVAL, IF ANY:

COTTONWOOD 36" STATE #1
1980' FSL & 1980' FWL SEC 36 T25SR2
EDDY CO. N.M.
DRILLED 5/97

13 3/8 48" J-40 @ 353' / CMT w/ 39050
353' CMT C.I.C

8 5/8" 32.3" J-55 @ 1860' / CMT w/ 100050
1860' CMT C.I.C

3100' : TOC

TUBING: 167 JTS 2 7/8 4.7" @ 5250' ±

PERFS: 5386-96 (11 SHOTS) (BRUSHY CANYON)

5470' : CEMENT RETAINER

PERFS: 5480-84 (8 SHOTS) SQUEEZED w/ 200 SX
(LWR BRUSHY CAN)

5526' : CEMENT RETAINER

PERFS: 5539-42 (4 HOLES) 5546-62 (17) 5564-69 (6)
SQUEEZED w/ 200 SX. (L. BRUSH CAN)

5680' : C.I.B.P. CAP w/ 20' CMT (LOADING B)

PERFS: 5720-32 (13 HOLES) 5736-40 (5 HOLES)
5742-52 (11 HOLES) (ANALOG)

5 1/2" 17" J-55 @ 5850' / CMT w/ 650 SX
TOC 3100' (C.B.L.)

5850'

PROPOSED PLUGGED WELLBORE

55K Cnr PLUG 3'-10'

30 SK CMT Plug 300'-400'
353' 13 3/8 @ 353

120 SK CMT PLUG 1510' - 1925'

1860' 8 5/8" @ 1860'

25 SX CMT f - 2075 - 2300

255K CMT plus 3775-5400

5386 PERFS 5386-5394

5396

5470 CMT RETAIN @ 5470

5480

5484 PERFS 5480-5484 502'D.

55-26

5-39

PERFS 5539-5569 SQZ'D

55-55

5680 CIBP @ 5680 CAP w/ 20' cur

5720

PERFS 5720-5752'

5752

5850 5 1/2 @ 5850