	-			20
			FORM APPROVED	
Form 3160-5 UNITED STATES				
une 1990)	DEPARTMENT O		Budget Bureau No. 1004-0135	
	BUREAU OF LAN	DMANAGEMENT	Expires: March 31, 1993 5. Lease Designation and Serial No.	
	SUNDRY NOTICES ANI	NMNM 29234 8. If Indian, Allottee or Tribe Name		
		· · · · · · · · · · · · · · · · · · ·		
	proposals to drill or to deepen o TION FOR PERMIT —" for such			
<u> </u>	SUBMIT IN TR	IPLICATE	7. If Unit or CA, Agreement Designation	
Type of Well				
X Oil Gas Well	INJECTION Other	a vivame or lease & wen		
Name of Operator		Lotos "10" Federal Well #3		
Sonat Exploration Co N Address and Telephone No.	lidland	9. 7AP1#		
10 W. Louisiana, Suite 5	00, Midland, TX 7970I (915) 684-63	Bl	30 015 29798 10. Field and Pool, or Exploratory Area	
	., T., R., M., or Survey Description)	Wildcat (Delaware)		
Surface: 660 FNL & TD:	660' FEL, Section 10, T24S, R3IE	11. County or Parish, State		
			Eddy County, NM	
CHECK APPROP	PRIATE BOX(s) TO INDICA	TE NATURE OF NOTICE, REPORT,	OR OTHER DATA	
TYPE OF SUBMISSION TYPE OF ACTION			1	
Notice of Int	ent	Abandonment	Change of Plans	
		Recompletion	New Construction	
X Subsequent	Report	Plugging Back	Non-Routine Fracturing	
		Casing Repair	Water Shut-Off	
Final Aband	onment Notice	Altering Casing	Conversion to Injection	
		X Spud/surf. csg./long string/TD	Dispose Water	
			(Note: Report results of multiple completion on Well	
Describe Proposed or Comple	ated Operations (Clearly state all pertinent	details, and give pertinent dates, including estimated dat	Completion or Recompletion Report and Log form.) te of starting any proposed work. If well is	
directionally drilled, give s	ubsurface locations and measured and tru	e vertical depths for all markers and zones pertinent to the	his work.)*	
	11/14.2/4" bit_drilled to 685'	, ran 17 jts 11 3/4", 42# WC-40 casing,	cemented with 390 sx CI C	
1-22-98: Spud we	1 W/14 5/4 Dit, utilied to 085	x CI C w/2% CaCl, plug down @ 4:15	am circulated II0 sx to pit	
	sted to 1000# for 30 minsO	N. 	C w/6% del 5% salt	
1-29-98: Ran 423	7 OF 8 5/8 , 24#, N-55 Casing	, cemented with I325 sx 35/65 POZ C	airculated 394 sx to pit	
		CaCl, plug down @ 12:15 am, I-29-98,	circulated 394 SX to pit.	
ND BOP	& set slips, weld on head, ni	pplea up BOP.		
2-6-98: Total dep	th: 8450', ran 8442' of 5 1/2"	, K-55 casing, cemented with 1st stage	e: 600 sx 50/50 POZ	
"H" w/2%	5 gel, 5% salt & I/4 FC, 2nd s	tage: 450 sx 50/50 POZ "H", w/2% ge	el, 5% sait & 1/4 FC,	
		ns - 15 bbls/62 sx, 2nd stage- did not	circulate, rig	
released	@ 8:00 pm 2-7-98.			
			b .2	
	\sim			
I hereby certify that the forege	ing is true and correct			
/1.1	SHA .	Ann E. Ritchie		
Signed			Date 5-14-98	
(This space for Federal or Stat	te office use)			
Approved by Conditions of approval, if any:	Title		Date	
e 18 U.S.C. Section 1001, mak	tes it a crime for any person knowingly and to any matter within its jurisdiction.	willfully to make to any department or agency of the Uni	ited States any false, fictitious or fraudulent	
		See Instruction on Reverse Side		<u> </u>
