015/

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

	SUNDRY NOTICES	NM-89172 6. If Indian, Allottee or Tribe Name	
Do no	ot use this form for proposals to di Use "APPLICATION F		
	SUBMIT	7. If Unit or CA, Agreement Designation	
	of Well		
X	Oil Gas Other	8. Well Name and No.	
	of Operator	Patton 17 Federal No. 7	
	Producing Company	9. API Well No.	
	ss and Telephone No. Box 10340, Midland ,TX 79702-7340 (30-015-29904	
. Locati	on of Well (Footage, Sec., T., R., M., or Survey De	10. Field and Pool, or Exploratory Area Poker Lake Delaware	
2075	'FNL & 2600' FEL, Section 17, T24S, R	11. County or Parish, State	
		Eddy County, NM	
2.	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OF	R OTHER DATA
	TYPE OF SUBMISSION	TYPE OF ACTION	
	Notice of Intent	Abandonment	Change of Plans
	·	Recompletion	New Construction
	Subsequent Report	Plugging Back	☐ Non-Routine Fracturing
	Final Abandonment Notice	Casing Repair	Water Shut-Off
		Altering Casing	Conversion to Injection
		Other Set Inter & Prod Csg	Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work.)*

Intermediate Csg - Drld 9-7/8" hole to 650' to 4250'. TD reached 1245 hrs CDT 5/28/98. Ran 104 jts 7-5/8" 26.40# J-55 ST& C csg. Float shoe @ 4250'. Float collar @ 4200'. Stage tool @ 2504'. BJ cmt'd w/ 340 sxs BJ Lite @ 12.4 ppg. Drop plug & disp cmt. Drop bomb & open stage tool @ 2504'. Circ 5 hrs between stages. Cmt 2nd stage w/ 750 sxs BJ Lite @ 12.4 ppg followed by 100 sxs Cl "C" @ 14.8 ppg. Plug down @ 0600 hrs CDT 5/29/98. Recov 196 sxs excess cmt. ND BOP's & make cut-off. Weld on wellhead & test to 2000 psi.

TD & Production Csg - Drld 6-3/4" hole to 8320'. TD reached @ 0145 hrs CDT 6/05/98. Logged well w/ Western Atlas. Ran 195 jts 4-1/2" 11.60# J-55 & N-80 LT&C csg. Float shoe @ 8320'. Float collar @ 8277'. DV tool @ 5999'. BJ cmt'd 1st stage w/ 725 sxs Cl "H" + .3% FL52 + .3% CD32 + .15% SMS + .1% R3 @ 15.7 ppg. Drop plug & displace cmt. Drop bomb & open DV tool. Circ 5 hrs between stages. Recov 150 sxs excess cmt. Cmt 2nd stage w/ 410 sxs BJ Lite @ 12.4 ppg followed by 100 sxs Cl "C" @ 14.8 ppg. Plug down @ 1745 hrs CDT 6/07/98. TOC @ 3375'. ND BOP's & make cut-off. Weld on wellhead & test to 2500 psi.

14. I hereby county that the foregoing is true and correct							
Signed January mas	Title	Division Operaions Engineer	Date	07/22/98			
(This space for Federal or State office use)							
Approved by Conditions of approval, if any:	Title		Date _				

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.