Form 3160-5		ED STATES		I		RM APPROVED		
(August 1999)	TED STATES OIL C S. DEPARTMENT OF THE INTERIOR N.M. DIV-DIS			5. I Dict	2 (15 lor	MB No. 1004-0135		
	BUREAU OF LAND MANAGEMENT 1301 W. Grand A SUNDRY NOTICES AND REPORTS ON WELLS Artesia. NM 88					s November 30, 2000		
			Adoolo NA		5 Lease Serial No).		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					NM-94589 6. If Indian, Allottee or Tribe Name			
dı	anuoned wen. Use Fon	11 3 100-3 (AFB) 101 300	in proposais.		o, in a lotant Palotte			
· · · 4	3)			ŀ				
					7. If Unit or CA/A	greement, Name and/or No.		
SUBMIT IN TRIPLICATE - Other Instructions on reverse side								
1. Type of Well		/:		5	8. Well Name and	No.		
Oil Well	X Gas Well	Other /	а ¹		Chosa ATR I			
2. Name of Operator				5.5	9. API Well No			
Yates Petroleum Corporation (c) (j) (j)<				\	30-015-3121	i, or Exploratory Area		
3a Address 105 S. 4th Street - A	Artesia NM 88210	505-748-1471	c A.	\$/	IU. FIEId and Fud	, or exploratory Alea		
4. Location of Well (<i>Footage</i> , Sec., T.,R., M., or Survey Description)					Chosa Draw Morrow			
2250' FSL and 1060' FWL Section 8-T25S-R26E					11. County or Parish, State			
			URE OF NOTICE, REPO					
TYPE OF SUMISSION		5) TO INDICATE NAT	TYPE OF ACTION			<u> </u>		
			Production (Start/Resume		Water Shut-Off			
Notice of Intent	Acidize	Deepen		*' L) 				
X Subsequent Report	Alter Casing	Fracture Treat	Reclamation		Well Integrity			
Final Abandonment Notice	Casing Repair	Casing Repair New Construction Recomplete			X Other Spud, set and cement surface casing			
	Change Plans	Plug and Abandon	Temporarily Abandon	-	opud, set and			
	Convert to Injection	Plug Back		-				
13. Describe Proposed or Completed					turation thereof. If t	he proposal is to deepen		
or provide the Bond No. on file wit completion or recompletion in a ne reclamation, have been completed 5/10/01 - Spudded 26" ho Notified Paul Evans with 6/3/01 - Resumed drilling 6/4/01 - Reached TD of s Ran 10 joints (426.63') 13 Cemented with 200 sxs F (yld 1.89, wt 12.6). Tailed	h BLM/BIA. Required subsequent aw interval, a Form 3160-4 shall b d, and the operator has determined ble with rathole machine al the BLM of spud. 17-1/2" hole with rotary to surface hole at 421' at 7:30 3-3/8" H-40 48# casing set RFC-12-2 Class A + 3 pps	reports shall be filed within 30 d e filed once testing has been co d that the site is ready for final in t 8:00 AM. Set 40' of 20 bools at 7:00 PM. c) PM. t at 421'. Texas Pattern D24 + 2% S1 (yld 1.6, v S1 + 1/4 pps D130 (yld 2	" conductor pipe, cemented guide shoe set at 421'. Inse vt 14.2) and 150 sxs 35/65 F 1.89, wt 14.8).	ved operations s shail be filed to surface. ert float set	. If the operations re only after all require	esults in a multiple ments, including		
Drilled out at 10:15 PM. WOC 20 hours, 30 mins.								
Reduced hole to 12-1/4"	and resumed drilling.				MA			
I hereby certify that the foregoing	is true and correct					LES BABYAK DI EUM ENGINTER		
Name (Printed/Typed) Title Engineering Technicia						······		
Signature	••••••••••••••••••••••••••••••••••••••	······································	Date	Jinnoran		·		
Japan Milling	00		5-Mar-02		_			
	THIS	SPACE FOR FEDE	RAL OR STATE OFF	ICE USE	· · · · · · · · · · · · · · · · · · ·			
Approved by		······································	Title			Date		
A specified by								
Conditions of approval, if any, are the applicant holds legal or equita applicant to conduct operations to	Office							
Fitle 8 U.S.C. Section 1001 and	Title 43 U.S.C. Section 1212, mak	ke it a crime for any person know	vingly and willfully to make to any dep	partment or age	ency of the United S	ates any faise, fictitious		
or fraudulent statements or repre-	esentations as to any matter within	its jurisdiction						