

(August 1999)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

OMB No. 1004-0135

Expires November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

Oil Cons.
N.M. Div. Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other Instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Yates Petroleum Corporation

3a Address

105 S. 4th Street - Artesia, NM 88210

3b. Phone No. (include area code)

505-748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL and 1830' FEL Sec 6 T24S R31E

8. Well Name and No.

Adeline ALN Federal #10

9. API Well No.

30-015-27254

10. Field and Pool, or Exploratory Area

S. Sand Dunes Delaware

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Drill, set csg, cement</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operations results in a multiple completion or recomple in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

1/30/01 - Spud 26" conductor at 11:30 AM. Set 40' 20" conductor pipe. Ready mix to surface. Notified BLM Don Early.

2/9/01 - Spud with rotary tool at 9:30 PM. Notified BLM Duncan Whitlock of intent.

2/10/01 - 758' TD of 17-1/2" hole at 1:15 PM. Ran 17 jts (763.17') of 13-3/8" 48# J-55 csg set at 728'.

Texas Pattern notched guide shoe set at 727'. Insert float set at 682.48'.

Cemented with 450 sx Halliburton Light Premium Plus 1/4# flocele, 2% CaCl₂ (yld 1.89, wt 12.6) Tailed in 200 sx Premium Plus 2% CaCl₂ (yld 1.34, wt 14.8). Plug down at 8:15 PM. Bumped plug to 200 psi. Float held OK. Circ 175 sxs.

Note: Casing stuck 30' off bottom at 728'. Verbal permission given by Duncan Whitlock of BLM to cement csg off bottom.

2/12/01 - Drill cement plug at 1:45 AM. WOC time 29-1/2 hrs. Reduced hole to 11" and resume drilling.

2/16/01 - TD 11" hole at 12:45 PM. Ran 97 jts (4109.2') of 8-5/8" 32# J-55 csg set at 4104'. Float shoe set at 4102.5', float collar set

at 4058.48'. Cemented with 1000 sx interfill "C", 1/4# flocene (yld 2.45, wt 11.9) Tailed in with 250 sxs "C" 2% CaCl₂ (yld 1.34, wt 14.8)

2/17/01 - Plug down at 12:00 AM. Bumped plug to 1400 psi. Float held. Circ. 192 sxs. WOC

2/18/01 - Drilled cement plug shoe at 2:15 AM. WOC 26 hrs. 15 min. Reduced hole to 7-7/8".

2/24/01 - Reached TD at 8160'. Log well. Logger's TD 8160'. Prep to run csg.

ACCEPTED FOR RECORD

I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Susan Herpin

Signature

Title

Operations Technician

Date

16-Aug-01

AUG 27 2001

ALEXIS C. SWOBODA
PETROLEUM ENGINEER

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED
2001 AUG 23 AM 9:47
BUREAU OF LAND MGMT
ROSWELL OFFICE