

Location:	660' FNL
	660' FWL
Section:	36
Township:	24S
Range:	31E
County:	EDDY, NM

Elevations:	
GL:	3498'
DF:	3525.5'
KB:	3527'

Current Wellbore Diagram

Well ID Info:	
Refno:	
API No:	30-015-31889
L5/L6:	
Spud Date:	
Compl. Date:	

TBG DETAIL:	
KB	27.50
1 JT 2 3/8" 4.7# AB MOB	31.25
6' x 2 3/8" tbg sub	6.05
472 JTS 2 3/8" L-80 AB MOD	14585.68
6' x 2 3/8" tbg sub	6.10
2 JTS	62.51
O/O W/ 1.875" 'F' PROFILE	1.64
BAKER MODEL 'M' PKR	5.62
10' X 2 3/8" SUB	10.10
1.81" 'R' NIPPLE	1.02
10' X 2 3/8" SUB	10.10
GUN RELEASE	1.59
10' X 2 3/8" SUB	9.93
DEBRIS SUB	.81
10' X 2 3/8" SUB	10.12
FIRING HEAD	4.79
SAFETY SPACER	8.66
SCHLUM 3 3/8" TCP GUN	12.00
BULL PLUG	.75
EOT	14,796.22

Surf. Csg: 13 3/8"
48#
H-40
Set: @ 704'
With: 1060 SXS
Hole Size: 17 1/2"
Circ: YES
TOC @ SURF

Int. Csg: 9 5/8"
36#
K-55
Set: @ 4283'
With: 1940 SXS
Hole Size: 12 1/4"
Circ: YES
TOC @ SURF

Prod. Csg: 7"
26 & 29#
P-110
Set @ 12,790'
With: 3160 SXS
Hole Size: 8 3/4"
Circ: NO
TOC @ 4300'

Liner: 5"
18 & 23#
P-110
TOL @ 12,267'
Set @ 15,200'
With: 580 SXS

COTD: 14,915'
PBSD: 14,915'
TD: 15,200'
Updated: 15-May-02
By: J. M. LOVELL

BAKER RELIANT MODEL 'M' PKR @ 14719' →
W/ O/O TOOL 1.875" 'F' PROFILE
1.81" 'R' NIPPLE @ 14,736'
1.781" GUN RLSE @ 14,747'
PERFS: 14,782' - 14,794' →
CIBP @ 14,950' (CAPPED W/ 35' CMT) →
PERFS: 14,995' - 15,068' →
15,084' - 15,097' →

