

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-015-32281
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. VB-0520
Lease Name or Unit Agreement Name Sundance 4 State
Well No. 1
Pool name or Wildcat Sand Dunes Delaware South

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
Name of Operator Pogo Producing Company	
Address of Operator P. O. Box 10340, Midland, TX 79702-7340	
Well Location Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line Section 4 Township 24S Range 31E NMPM Eddy County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3414' GR	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: Circ Cmt ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pogo Producing Company plans to circulate cement on the above captioned well based on the following procedure:

1. POH w/ rods, pump & tubing.
2. Set RBP @ 5000'. Dump sand on RBP.
3. Perf (2) sqz holes @ 4800'. Est circ on 8-5/8" casing.
4. Set sqz pkr @ 4600'. Notify OCD of squeeze.
5. Circ cmt to surface using 600 sks lite "C" followed w/ 1/4# celloflake followed by 100 sks CI "C" w/ 2% CaCl2
6. Retrieve pkr. DO cmt. Retrieve RBP. Put well back on pump.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Cathy Tomberlin

TITLE

Sr. Operation Tech

DATE

07/15/02

TYPE OR PRINT NAME Cathy Tomberlin

(915)685-8100

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

JUL 18 2002

CONDITIONS OF APPROVAL, IF ANY: