Form 9-331 C
(May 1963)

N.M.O.C.D. COPY

SUBMIT IN T[illegible]ICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1425.

30-005-61098

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK
DRILL [X] DEEPEN [ ] PLUG BACK [ ]

b. TYPE OF WELL
OIL WELL [ ] GAS WELL [X] OTHER SINGLE ZONE [X] MULTIPLE ZONE [ ]

2. NAME OF OPERATOR
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR
1000 VAUGHN BLDG./MIDLAND, TX. 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*)
At surface
660' FSL & 660' FEL, UNIT P.
At proposed prod. zone
SAME

RECEIVED
AUG 26 1981
O. C. D.
ARTESIA, OFFICE

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*
14 MILES NORTHWEST OF ROSWELL.

5. LEASE DESIGNATION AND SERIAL NO.
NM 36651

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
CINDY FEDERAL

9. WELL NO.
4

10. FIELD AND POOL, OR WILDCAT
UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
UL-P
SEC. 25, T8S, R22E

12. COUNTY OR PARISH
CHAVES

13. STATE
NEW MEXICO

15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any)
660'/660'

16. NO. OF ACRES IN LEASE
1280

17. NO. OF ACRES ASSIGNED TO THIS WELL
160

18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT.
4000'

19. PROPOSED DEPTH
3500'

20. ROTARY OR CABLE TOOLS
ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)
3974' GR

22. APPROX. DATE WORK WILL START*
December 15, 1981

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12 1/4"	8 5/8"	24 #	1600	SURFACE
7 7/8"	4 1/2"	10.5#	3500	ISOLATE WATER, OIL & GAS

Propose to drill 12 1/4" hole to approximately 1600' to set 8 5/8" surface casing and cement to surface. Will nipple up ram type BOP's and reduce hole to 7 7/8" to drill to total depth. Drilling meduim will be air, foam, or mud as required. After log evaluation, 4 1/2" casing may be run and cemented with sufficient kinds and amounts to isolate and seal off any fresh water, oil, or gas zones encountered.

Gas Sales Are Dedicated.

RECEIVED
AUG 20 1981
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Posted
API + NL
9-4-81

XC: USGS (6), TLS, CEN RCDS, ACCTG, ROSWELL, MEC, LAND, PARTNERS, FILE.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED R. F. Mask TITLE REGULATORY COORDINATOR DATE 8-18-81

(This space for Federal or State office use)

PERMIT NO. ______ APPROVAL DATE ______

APPROVED
APPROVED BY (Orig. Sgd.) GEORGE H. STEWART TITLE ______ DATE ______
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions On Reverse Side

N MEXICO OIL CONSERVATION COMMISS

WELL LOCATION AND ACREAGE DEDICATION PLAT

All distances must be from the outer boundaries of the Section

Mesa Petroleum Co.		Cindy Federal	
P	25	8South	22East	Chaves
660 feet from the	South	660 feet from the	East	
3974.0'	ABO	UNDESIGNATED Abo	SE/4 160

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.

2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).

3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

Yes No If answer is "yes," type of consolidation _____

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

R. E. Mathis

R.E. MATHIS

REGULATORY COORDINATOR

MESA PETROLEUM CO.

8-17-81

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

June 22, 1981

Date Surveyed

John W. West

Certificate No. JOHN W. WEST 676
PATRICK A. ROMERO 6668
Ronald J. Eidson 3239

MESA PETROLEUM CO
CINDY FEDERAL #4
660' FSL, 660' FEL, SEC 25, T8S, R22E
CHAVES COUNTY, NEW MEXICO
LEASE NO. NM-36651

In conjunction with Form 9331-C, Application For Permit to Drill subject well, the following additional information is provided:

1. Applicable portions of the GENERAL REQUIREMENTS FOR OIL AND GAS OPERATIONS ON FEDERAL LEASES, Roswell District, Geological Survey of September 1, 1980 will be adhered to.

2. Geological markers are estimated as follows:

San Andres	Surface
Glorieta	582'
Yeso	767'
Tubb	2192'
Abo	2842'

3. Hydrocarbon bearing strata may occur in the ABO formation(s). No fresh water is expected to be encountered below 1000'.

4. The Casing and Blowout Preventer Program will be determined by hole conditions as encountered. (See Exhibit VI) Anticipate drilling with air or foam using ram type preventer and rotating head for well control. The 8 5/8" casing will be set at approximately 1600' to protect any fresh water zones and cemented to the surface. The 4 1/2" production casing will be set at total depth or shallower depending upon the depth of the deepest commercial hydrocarbon bearing strata encountered. Sufficient amounts and kinds of cement would be used to ensure any water, gas, or oil zones encountered are isolated and shut off down to the casing point, if run.

5. No drill stem tests or coring program is planned. The logging program may consist of a GR-CNL from surface to total depth and FDC from casing point to total depth.

6. Anticipated drilling time is ten days with completion operations to follow as soon as a completion unit is available.

MESA PETROLEUM CO
CINDY FEDERAL #4
660' FSL & 660' FEL, SEC 25, T8S, R22E
CHAVES COUNTY, NEW MEXICO
LEASE NO. NM - 36651



This plan is submitted with the Application for Permit to Drill the above described well. The purpose of this plan is to describe the location of the proposed well, the proposed construction activities and operational plan in both the actual and post drilling completion operations.

1. Existing Roads:

A. Exhibit I is a portion of a highway map showing the location of the proposed well as staked. The proposed well is approximately 14 miles northwest of Roswell, New Mexico.

B. Directions: travel north from Roswell on US Highway 285 to just before mile marker 117, turn west thru cattleguard and follow lease road westerly for 8 miles then north 2 miles. Take west fork 3/4 miles to the location.

2. Planned Access Road:

A. Length and width: The new access road will be 12' wide (20' ROW) and located adjacent to the ranch road.

(See Exhibit II)

B. Construction: The new road will be constructed by grading and topping with compacted caliche. The surface will be crowned, with drainage on both sides. (See Exhibit III)

C. Culverts, Gates and Cattleguards: None

D. Cut and Fill: In order for the location to be level, approximately 3' will be moved from the south to the north for fill.

3. Location of Existing Wells:

Existing wells within a one-mile radius are depicted by Exhibit IV.

4. Location of Existing and/or Proposed Facilities:

If the well proves to be commercial, the necessary production facilities, gas separation process equipment and tank battery, will be installed on the drilling pad.

5. Location and Type of Water Supply:

It is planned to drill the proposed well with
will be obtained from commercial sources and will be trucked to the wellsite over the existing roads and proposed access road shown on Exhibits I and II.

6. Source of Construction Materials:

Caliche for surfacing the road and wellsite pad will be obtained by the dirt contractor from an approved pit. Probable pit is located: unknown.

7. Methods of Handling Waste Disposal:

A. Drill cuttings will be disposed of in the reserve pits.

B. Drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry.

C. All pits will be fenced with normal fencing material to prevent livestock from entering the area.

D. Water produced during operations will be collected in tanks until hauled to an approved disposal system, or separate disposal application will be submitted to the USGS for approval.

E. Current laws and regulations pertaining to the disposal of human waste will be complied with.

F. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind.

G. All trash and debris will be buried or removed from the wellsite within 30 days after finished and/or completion operations.

8. Ancillary Facilities: None required.

9. Wellsite Layout:

A. Exhibit V shows the relative location and dimensions of the well pad, reserve pits, and major rig components. The pad and pit area has been staked and flagged.

B. Some leveling of the wellsite may be required. See Exhibit III for additional details.

C. The reserve pit will not be lined.

10. Plans for Restoration of the Surface:

A. After completion of drilling and/or completion operations all equipment and other material not needed for operations will be removed. Pits will be filled and location cleaned of all trash and junk to leave the wellsite in an aesthetically pleasing a condition as possible.

B. Any unguarded pits containing fluids will be fenced until they are filled.

C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the Bureau of Land Management and the United States Geological Survey will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment, if drying conditions permit.

11. Other Information:

A. Topography: See NMAS, INC. Archaeological Report.

B. Soil: The topsoil at the wellsite is sandy loam.

C. Flora and Fauna: See NMAS, Inc. Archaeological Report for vegetative types.

D. Ponds and Streams: Salt Creek is 3/4 mile to the northeast.

E. Residences and Other Structures: Special precautions are being taken to protect various burried water lines in the vicinity of this well.

F. Land Use: Grazing.

G. Surface Ownership: The wellsite is on Federal surface.

H. NMAS, Inc. has conducted an archaeological study of this site and provides this report to interested parties.

12. Operator's Representatives:

A. The field representatives responsible for assuring compliance with the approved surface use and operations plan are as follows:

J. James
P. O. Box 298
Roswell, New Mexico
(505-622-0992) - Office
(505-622-0234) - Home

W. R. Miertschin
1000 Vaughn Building
Midland, Texas 79701
(915-683-5391) - Office
(915-682-6535) - Home

13. Certification:

I hereby certify that I, or person under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge true and correct; and, that the work associated with the operations proposed herein will be performed by Mesa Petroleum Co. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.

9-18-91
DATE

Michael P. Houston
MICHAEL P. HOUSTON
OPERATIONS MANAGER



EXHIBIT I

AREA ROADWAYS FOR PROPOSED
CINDY FEDERAL #4



EXHIBIT II

TOPOGRAPHIC FEATURES FOR
PROPOSED CINDY FEDERAL #4

R - O - W 16'



ROADWAY CROSS SECTION

Horizontal Scale 1" = 3'



LOCATION CROSS SECTION

Horizontal Scale 1" = 50'

MESA PETROLEUM CO.
PERMIAN BASIN DIVISION

EXHIBIT III

LOCATION CONSTRUCTION

BY: REM DRAWN BY: MLE
DATE: 3-8-82 SCALE: AS NOTED


MESA
PETROLEUM CO.
PERMIAN BASIN DIVISION
EXHIBIT IV
ONE-MILE RADIUS LAND MAP FOR
PROPOSED CINDY FEDERAL #4



N

MESA
PETROLEUM CO.
PERMIAN BASIN DIVISION

EXHIBIT V

FOR PROPOSED CINDY FEDERAL #4

Blow-out Preventers hydril and choke manifold are all 900 Series



3,000 PSI WORKING PRESSURE
BLOW-OUT PREVENTER HOOK-UP



3,000 PSI WORKING PRESSURE
KILL, CHOKE, AND FILL CONNECTIONS

DETAIL OF 4" FLOW LINE CHOKE ASSEMBLY

Minimum assembly for 3,000 PSI working pressure will consist of three preventers. The bottom and middle preventers may be Cameron.

NOTE: HYDRIL not installed on shallow-low pressure wells. RAM type BOPs are API 10" X 3000 PSI

MESA PETROLEUM CO.
PERMIAN BASIN DIVISION

E X H I B I T

V I

BY: DRAWN BY:
DATE: SCALE: