

SUPPLEMENTAL DRILLING DATA

McKAY OIL CORPORATION  
Westfork Federal #14  
NW/4NE/4 Sec. 5-5S-22E  
Chaves County, N.M.

NM 32312

The following items supplement Form 9-331C in accordance with instructions contained in NTL-6.

1. SURFACE FORMATION: San Andres
2. ESTIMATED TOPS OF GEOLOGIC MARKERS:
  - Yeso - 930'
  - Tubb - 2448'
  - Abo - 3138'
3. ESTIMATED DEPTHS TO WATER, OIL OR GAS FORMATION:
  - Fresh water - In surface formations above 600'
  - Gas - In Abo formation below 3138'
4. PROPOSED CASING PROGRAM: See Form 9-331C
5. PRESSURE CONTROL EQUIPMENT: Blowout preventer stack will consist of at least a double-ram blowout preventer rated to ~~2000~~ <sup>2000</sup> #WP. A sketch of the BOP is attached.
6. CIRCULATING MEDIUM:
  - 0'- 600' Lime and gel, spud mud, viscosity 32 to 34 seconds.
  - 600'- 2938' Fresh water
  - 2938'- TD Start mudding up at 2938'; viscosity 36 to 38 seconds; water loss 10 cc or less; 3-5% Diesel; 2 KCLMud additives will be used to control water loss.
7. AUXILIARY EQUIPMENT: full-opening drill string safety valve fit the drill string in use, will be kept on the rig floor at all times.