

## SUPPLEMENTAL DRILLING DATA

McKAY OIL CORPORATION  
West Fork Federal Unit #9  
SW1/4SE1/4 Sec. 24-5S-21E  
Chaves County, N.M.

NM 32311

The following items supplement Form 9-331C in accordance with instructions contained in NTL-6.

1. SURFACE FORMATION: San Andres
2. ESTIMATED TOPS OF GEOLOGIC MARKERS:

Yeso	- 853'
Tubb	- 2383'
Abo	- 3063'
3. ESTIMATED DEPTHS TO WATER, OIL OR GAS FORMATION:

Fresh water	- In surface formations above 600'
Gas	- In Abo formation below 3063'
4. PROPOSED CASING PROGRAM: See Form 9-331C
5. PRESSURE CONTROL EQUIPMENT: Blowout preventer stack will consist of at least a double-ram blowout preventer rated to ~~3000~~ <sup>2000</sup> WP. A sketch of the BOP is attached. <sup>2000</sup>
6. CIRCULATING MEDIUM:

0'- 700'	Lime and gel, spud mud, viscosity 32 to 34 seconds.
700'- 2963	Fresh water
2963'- TD	Start mudding up at 2963'; viscosity 36 to 38 seconds; water loss 10 cc or less; 3-5% Diesel; 2 KCL

Mud additives will be used to control water loss.
7. AUXILIARY EQUIPMENT: full-opening drill string safety valve fit the drill string in use, will be kept on the rig floor at all times.

